



Busbar support, for CI enclosure 375mm , 2x hxd=30x10mm

Part no. **SH1005/4**
Catalog No. **062993**

EL-Nummer
(Norway) **2502260**

Delivery program

Product range			xEnergy Safety Ci
Basic function			Prepared enclosures
Product function			Accessories for busbar enclosures
Accessories			Busbar support
Function			For use between two enclosures
Description			Component mounting possible on busbar Interval between busbar supports max. 375 mm
Interval between busbar centres		mm	50
Width		mm	375
Rated operational current	I_e	A	1000
For use with			L1, L2, L3: 2 x 30 x 10; PE, N: 30 x 10
For use with			CI48... CI45... CI44...

Technical data ETIM 7.0

Energy distribution systems (EG000015) / Busbar support (EC001166)			
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Busbar support (ecl@ss10.0.1-27-40-06-07 [AC0377011])			
Number of poles			5
Max. rated current		A	1000
Busbar distance		mm	50

Additional product information (links)

allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 model certification xEnergy Safety Ci	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 Save time – we assist you with expert pre-assembly	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
allowInterrupt=1&RevisionSelectionMethod=LatestReleased&noSaveAs=0&Render=1 product information xEnergy Safety Ci	http://www.eaton.eu/DE/ecm/idcplg?IdcService=GET_FILE&...
tool for calculating the power loss for switching device combinations	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/TCTool/index.htm
configurator - xEnergy family	http://www.eaton.eu/DE/Europe/Electrical/CustomerSupport/ConfigurationTools/xEnergyMainSupport/index.htm