

Sensor-switched LED floodlight

Spot ONE

Sensor Connect

EAN 4007841 058630

Article number 058630



LED

20.000 h

3000 K

3000K
warm-white



38°



infrared sensor
90°



max. 10 m



IP44



2 - 2000 lux (via
App)



manual override
4h



energy saving

3 years

manufacturer's
warranty
[steinel.de/garantie3y](https://www.steinel.de/garantie3y)

Function description

Intelligent and convenient. Modern swivelling LED wall spot ONE Sensor Connect with 90° infrared motion detector (10 m reach). Interconnectable via Bluetooth in next to no time and adjustable via the free app: light-level threshold (2-2000 lux), time setting (5 s – 60 min), ON and OFF times, convenient light grouping. 512 lm from 7,9 W. Includes replaceable GU-10 LED lamp.

Spot ONE

Sensor Connect

EAN 4007841 058630


Article number 058630

Technical specifications

Dimensions (L x W x H)	175 x 97 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	7,9 W
Interconnection	Yes
Interconnection via	Bluetooth
Slave modeselectable	Yes
Luminous flux	512 lm
Efficiency (without shade/diffuser)	74 lm/W
Gesamtprodukt Effizienz	64,8 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
Base	GU10
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No

Reach, radial	r = 2 m (3 m ²)
Reach, tangential	r = 10 m (79 m ²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Main light adjustable	No
Functions	Timer, Master/slave override
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Installation site	wall
Version	Sensor Connect
PU1, EAN	4007841058630

Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

Dimension Drawing

