



199283  
DILM17-11(RDC24)-PI

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as  
per IEC/EN 61439

Technical data ETIM 7.0

Approvals

Characteristics

Dimensions

## DELIVERY PROGRAM

Product range  
Contactors

Application  
Contactors for Motors

Subrange  
Contactors up to 170 A, 3 pole

Utilization category  
AC-1: Non-inductive or slightly inductive loads,  
resistance furnaces  
AC-3/AC-3e: Normal AC induction motors: Starting,  
switching off while running  
AC-4: Normal AC induction motors: starting,  
plugging, reversing, inching



Notes  
Also suitable for motors with efficiency class IE3.

Connection technique  
Push in terminals

Number of poles  
3 pole

### Rated operational current

AC-3  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
380 V 400 V [ $I_e$ ]  
17 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
40 A

AC-1  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
32 A

AC-1  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
88 A

AC-1  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
80 A

### Max. rating for three-phase motors, 50 - 60 Hz

AC-3  
220 V 230 V [ $P$ ]  
4.7 kW



Connection to SmartWire-DT  
yes  
in conjunction with DIL-SWD SmartWire DT  
contactor module

Frame size  
2

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947, VDE 0660, UL, CSA

Operating frequency, mechanical  
DC operated [Operations/h]  
5000


Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Open  
-25 - +60 °C

Ambient temperature  
Enclosed  
- 25 - 40 °C

Ambient temperature  
Storage  
- 40 - 80 °C

Mounting position



Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms

Main contacts  
N/O contact  
10 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
7 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
5 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Main contacts  
N/O contact  
6.9 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/O contact  
5.3 g

Mechanical shock resistance (IEC/EN 60068-2-27)  
when tabletop-mounted  
Half-sinusoidal shock, 10 ms  
Auxiliary contacts  
N/C contact  
3.5 g

Degree of Protection  
IP20

Protection against direct contact when actuated  
from front (EN 50274)  
Finger and back-of-hand proof

Altitude  
Max. 2000 m

Weight  
DC operated  
0.55 kg

Spring-loaded terminal connection  
Tool  
Standard screw driver  
3.0 x 0.5

Push-in terminals  
Terminal capacity main cable  
Solid  
1 x (1 - 6)  
2 x (1 - 6) mm<sup>2</sup>

Push-in terminals  
Terminal capacity main cable  
flexible  
1 x (1 - 10)  
2 x (1 - 6) mm<sup>2</sup>

Push-in terminals  
Terminal capacity main cable  
flexible with ferrules  
1 x (1 - 6)  
2 x (1 - 4) mm<sup>2</sup>

Push-in terminals  
Terminal capacity main cable  
flexible with ultrasonic welded busbar end  
1 x (1 - 10)  
2 x (1 - 6) mm<sup>2</sup>

Push-in terminals  
Terminal capacity main cable  
flexible with uninsulated wire end ferrule  
1 x (1 - 6)  
2 x (1 - 6) mm<sup>2</sup>

Push-in terminals  
Terminal capacity main cable  
Solid or stranded  
18 - 8 AWG

Push-in terminals  
Terminal capacity main cable  
Stripping length  
12 mm

Push-in terminals  
Terminal capacity main cable  
Standard screw driver  
3.0 x 0.5

Push-in terminals

Terminal capacity control circuit cables  
Solid  
1 x (0,5 - 2,5)  
2 x (0,5 - 2,5) mm<sup>2</sup>

Push-in terminals  
Terminal capacity control circuit cables  
flexible  
1 x (0,5 - 2,5)  
2 x (0,5 - 2,5) mm<sup>2</sup>

Push-in terminals  
Terminal capacity control circuit cables  
flexible with ferrules  
1 x (0,5 - 1,5)  
2 x (0,5 - 1,5) mm<sup>2</sup>

Push-in terminals  
Terminal capacity control circuit cables  
flexible with ultrasonic welded busbar end  
1 x (0,5 - 2,5)  
2 x (0,5 - 2,5) mm<sup>2</sup>

Push-in terminals  
Terminal capacity control circuit cables  
flexible with uninsulated wire end ferrule  
1 x (0,5 - 2,5)  
2 x (0,5 - 2,5) mm<sup>2</sup>

Push-in terminals  
Terminal capacity control circuit cables  
Solid or stranded  
20 - 14 AWG

Push-in terminals  
Terminal capacity control circuit cables  
Stripping length  
10 mm

Push-in terminals  
Tool  
Standard screw driver  
3.0 x 0.5 mm

## Main conducting paths

Rated impulse withstand voltage [U<sub>imp</sub>]  
8000 V AC

Overvoltage category/pollution degree

Rated insulation voltage [U]  
690 V AC

Rated operational voltage [U<sub>e</sub>]  
690 V AC

Safe isolation to EN 61140  
between coil and contacts  
400 V AC

Safe isolation to EN 61140  
between the contacts  
400 V AC

Making capacity (p.f. to IEC/EN 60947) [Up to 690 V]  
238 A

Breaking capacity  
220 V 230 V  
170 A

Breaking capacity  
380 V 400 V  
170 A

Breaking capacity  
500 V  
170 A

Breaking capacity  
660 V 690 V  
120 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
400 V [gG/gL 500 V]  
35 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "2" coordination  
690 V [gG/gL 690 V]  
35 A



Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
400 V [gG/gL 500 V]  
63 A

Short-circuit rating  
Short-circuit protection maximum fuse  
Type "1" coordination  
690 V [gG/gL 690 V]  
50 A

## AC

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 40 °C [ $I_{th} = I_e$ ]  
40 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 50 °C [ $I_{th} = I_e$ ]  
38 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 55 °C [ $I_{th} = I_e$ ]  
37 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
Open  
at 60 °C [ $I_{th} = I_e$ ]  
35 A

AC-1  
Rated operational current  
Conventional free air thermal current, 3 pole, 50 -  
60 Hz  
enclosed [ $I_{th}$ ]  
32 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
open [ $I_{th}$ ]  
88 A

AC-1  
Rated operational current  
Conventional free air thermal current, 1 pole  
enclosed [ $I_{th}$ ]  
80 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
Notes  
At maximum permissible ambient temperature  
(open.)  
Also tested according to AC-3e.

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [ $I_e$ ]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
440V [ $I_e$ ]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz

500 V [I<sub>e</sub>]  
17 A

AC-3  
Rated operational current  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [I<sub>e</sub>]  
12 A

AC-3  
Motor rating [P]  
220 V 230 V [P]  
4.7 kW

AC-3  
Motor rating [P]  
240V [P]  
5 kW

AC-3  
Motor rating [P]  
380 V 400 V [P]  
7.5 kW

AC-3  
Motor rating [P]  
415 V [P]  
8.7 kW

AC-3  
Motor rating [P]  
440 V [P]  
9.5 kW

AC-3  
Motor rating [P]  
500 V [P]  
11 kW

AC-3  
Motor rating [P]  
660 V 690 V [P]  
10.5 kW

AC-4  
Open, 3-pole: 50 – 60 Hz  
220 V 230 V [I<sub>e</sub>]  
10 A

AC-4

Open, 3-pole: 50 – 60 Hz  
240 V [ $I_e$ ]  
10 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
380 V 400 V [ $I_e$ ]  
10 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
415 V [ $I_e$ ]  
10 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
440 V [ $I_e$ ]  
10 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
500 V [ $I_e$ ]  
10 A

AC-4  
Open, 3-pole: 50 – 60 Hz  
660 V 690 V [ $I_e$ ]  
8 A

AC-4  
Motor rating [P]  
220 V 230 V [P]  
2.5 kW

AC-4  
Motor rating [P]  
240 V [P]  
3 kW

AC-4  
Motor rating [P]  
380 V 400 V [P]  
4.5 kW

AC-4  
Motor rating [P]  
415 V [P]  
5 kW

AC-4

Motor rating [P]  
440 V [P]  
5.5 kW

AC-4  
Motor rating [P]  
500 V [P]  
6 kW

AC-4  
Motor rating [P]  
660 V 690 V [P]  
6.5 kW

### Current heat loss

3 pole, at  $I_{th}$  (60°)  
7.9 W

Current heat loss at  $I_e$  to AC-3/400 V  
2.1 W

Impedance per pole  
2.7 mΩ

### Magnet systems

Voltage tolerance  
DC operated [Pick-up]  
 $0.7 - 1.2 \times U_c$

Voltage tolerance  
Notes  
RDC 24 ( $U_{min}$  24 V DC/ $U_{max}$  27 V DC)  
Example:  $U_S = 0.7 \times U_{min} - 1.2 \times U_{max} / U_S = 0.7 \times 24V - 1.2 \times 27V$  DC

Voltage tolerance  
DC operated [Drop-out]  
 $0.15 - 0.6 \times U_c$

Voltage tolerance  
Notes  
at least smoothed two-phase bridge rectifier or  
three-phase rectifier

Power consumption of the coil in a cold state and

1.0 x  $U_S$   
DC operated [Pick-up]  
12 W

Power consumption of the coil in a cold state and  
1.0 x  $U_S$   
DC operated [Sealing]  
0,9 W

Duty factor  
100 % DF

Changeover time at 100 %  $U_S$  (recommended  
value)  
Main contacts  
DC operated  
Closing delay  
Closing delay  
47 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
Main contacts  
DC operated  
Opening delay  
Opening delay  
30 ms

Changeover time at 100 %  $U_S$  (recommended  
value)  
Arcing time  
10 ms

## Electromagnetic compatibility (EMC)

Emitted interference  
According to EN 60947-1

Interference immunity  
According to EN 60947-1

## Rating data for approved types

Switching capacity  
Maximum motor rating  
Three-phase  
200 V  
208 V  
5 HP

Switching capacity  
Maximum motor rating  
Three-phase  
230 V  
240 V  
5 HP

Switching capacity  
Maximum motor rating  
Three-phase  
460 V  
480 V  
10 HP

Switching capacity  
Maximum motor rating  
Three-phase  
575 V  
600 V  
15 HP

Switching capacity  
Maximum motor rating  
Single-phase  
115 V  
120 V  
2 HP

Switching capacity  
Maximum motor rating  
Single-phase  
230 V  
240 V  
3 HP

Switching capacity  
General use  
40 A

Auxiliary contacts  
General Use  
AC  
600 V

Auxiliary contacts  
General Use  
AC  
10 A

Auxiliary contacts  
General Use  
DC

250 V

Auxiliary contacts  
General Use  
DC  
1 A

Short Circuit Current Rating  
Basic Rating  
SCCR  
5 kA

Short Circuit Current Rating  
Basic Rating  
max. Fuse  
125 A

Short Circuit Current Rating  
Basic Rating  
max. CB  
125 A

## DESIGN VERIFICATION AS PER IEC/EN 61439

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+60 °C

## TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)

Electric engineering, automation, process control engineering / Low-voltage switch technology /  
Contactor (LV) / Power contactor, AC switching (ecl@ss10.0.1-27-37-10-03 [AAB718015])

Rated control supply voltage  $U_s$  at AC 50-HZ  
0 - 0 V

Rated control supply voltage  $U_s$  at AC 60-HZ



0 - 0 V

Rated control supply voltage  $U_s$  at DC  
24 - 27 V

Voltage type for actuating  
DC

Rated operation current  $I_e$  at AC-1, 400 V  
45 A

Rated operation current  $I_e$  at AC-3, 400 V  
17 A

Rated operation power at AC-3, 400 V  
7.5 kW

Rated operation current  $I_e$  at AC-4, 400 V  
10 A

Rated operation power at AC-4, 400 V  
4.5 kW

Rated operation power NEMA  
0 kW

Modular version  
No

Number of auxiliary contacts as normally open  
contact  
1

Number of auxiliary contacts as normally closed  
contact  
1

Type of electrical connection of main circuit  
Spring clamp connection

Number of normally closed contacts as main  
contact  
0

Number of main contacts as normally open contact  
3

## APPROVALS

Product Standards  
IEC/EN 60947-4-1; UL 60947-4-1; CSA - C22.2 No.  
60947-4-1-14; CE marking

UL File No.  
E29096

UL Category Control No.  
NLDX

CSA File No.  
012528

CSA Class No.  
2411-03, 3211-04

North America Certification  
UL listed, CSA certified

Specially designed for North America  
No

## CHARACTERISTICS

Accessories  
1: Overload relay  
2: Suppressor  
3: Auxiliary contact modules

Switching conditions for non-motor consumers, 3  
pole, 4 pole  
Operating characteristics  
Non inductive and slightly inductive loads  
Electrical characteristics  
Switch on: 1 x rated operational current  
Switch off: 1 x rated operational current

Utilization category  
100 % AC-1  
Typical examples of application  
Electric heat

## DIMENSIONS

