

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NZM2/3-XA24AC/DC - Shunt release, 24VAC/DC



259754 NZM2/3-XA24AC/DC

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Approvals](#)

259754 NZM2/3-XA24AC/DC

Shunt release, 24VAC/DC

EL-Nummer (Norway)

4315548

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple.

Delivery program

Product range

Accessories

Accessories

Shunt release

Accessories

Shunt releases

Standard/Approval

UL/CSA, IEC

Construction size

NZM2/3

Description

Switches are tripped by a voltage pulse or by the application of uninterrupted voltage.

If the shunt trip is live, contact with the circuit breaker's primary contacts is prevented when switched on.

Shunt releases cannot be installed simultaneously with NZM...-XHIV... early-make auxiliary contact or NZM...-XU... undervoltage release.

Connection type

With bolt connection

Auxiliary contacts

without auxiliary contact

Rated control voltage [U_s]

24 V AC/DC V

For use with

NZM2(-4), N(S)2(-4)

NZM3(-4), N(S)3(-4)

Technical data

Shunt release

Rated control voltage [U_s] AC [U_s]

24-24 V AC

Rated control voltage [U_s] DC [U_s]

24-24 V DC

Frequency

50/60/200/400, DC Hz

Operating range AC [$\times U_s$]

0.7 - 1.1

Operating range DC [$\times U_s$]

0.7 - 1.1

Power consumption Pick-up AC/DC

2.5 VA/W

Power consumption Power consumption Pick-up = Sealing

2.5 VA/W

Maximum opening delay (response time until opening of the main contacts)

20 ms

Maximum duty factor

∞ ms

Minimum command time

10 ... 15 ms

Terminal capacities Solid or flexible conductor, with ferrule

1 $\times$ (0,75 - 2,5)

2 $\times$ (0,75 - 2,5) mm²

Terminal capacities

1 $\times$ (18 ... 14)

2 $\times$ (18 ... 14) AWG

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ec1@ss10.0.1-27-37-04-18 [AKF016013])

Rated control supply voltage U_s at AC 50Hz

24 - 24 V

Rated control supply voltage U_s at AC 60Hz

24 - 24 V

Rated control supply voltage U_s at DC

24 - 24 V

Voltage type for actuating

AC/DC

Initial value of the undelayed short-circuit release - setting range

0 A

End value adjustment range undelayed short-circuit release

0 A

Type of electric connection

Screw connection

Number of contacts as normally open contact

0

Number of contacts as normally closed contact

0

Number of contacts as change-over contact

0

Suitable for power circuit breaker

Yes

Suitable for off-load switch

Yes

Suitable for motor safety switch

No

Suitable for overload relay

No

Approvals

Product Standards

UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking

UL File No.

E140305

UL Category Control No.

DIHS

CSA File No.

022086


CSA Class No.

1437-01

North America Certification

UL listed, CSA certified

Wiring diagram




123S017

Line drawing


Shunt release

3D drawing



123431

Line drawing
Undervoltage releases



1234520

Line drawing
Undervoltage releases, shunt releases

Product photo



1230PIC-1370

Photo

Instruction Leaflet

- [NZM2/3 XHIV \(IL012141ZU\)](#)
IL012141ZU
(PDF, 03/20, Language independent)

CAD data

edz files

- [DA-CE-ETN.NZM2_3-XA24AC_DC](#)
File
(Web)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

