



**265783**  
**NZMN4-ME550**

Overview

Specifications

Resources



Delivery program

Technical data

Design verification as  
per IEC/EN 61439

Technical data ETIM 7.0

Characteristics

Dimensions

## DELIVERY PROGRAM

Product range  
Circuit-breaker

Protective function  
MOTOR protection



Standard/Approval  
IEC

Installation type  
Fixed

Release system  
Electronic release

Construction size  
NZM4

#### Description

IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

R.m.s. value measurement and "thermal memory"  
Adjustable time delay setting to overcome current peaks  $t_r$  at  $6 \times I_r$  also infinity (without overload releases)

All AC-3 rating data applies to direct switching by the circuit-breaker under normal operating conditions. If, for example, a contactor takes over AC-3 switching under normal operating conditions, the full rated uninterrupted current applies to the circuit-breaker,  $I_n = I_u$ .

Number of poles  
3 pole

Standard equipment  
Screw connection

### Switching capacity

400/415 V 50 Hz [ $I_{cu}$ ]  
50 kA

Rated current = rated uninterrupted current [ $I_n = I_u$ ]  
550 A

### Setting range

Overload trip  
 [ $I_r$ ]  
275 - 550 A

Short-circuit releases  [ $I_{rm}$ ]  
Non-delayed  [ $I_r = I_n \times \dots$ ]  
2 - 14

### Motor rating AC-3 50/60 Hz [P]

380 V 400 V [P]  
315 kW

660 V 690 V [P]

560 kW

### Motor rating AC-3 50/60 Hz [P]

400 V [P]  
315 kW

660 V 690 V [P]  
560 kW

### Rated operational current AC-3 50/60 Hz [I<sub>e</sub>]

400 V [I<sub>e</sub>]  
544 A

690 V  
550 A

## TECHNICAL DATA

### General

Standards  
IEC/EN 60947

Protection against direct contact  
Finger and back of hand proof to VDE 0106 Part  
100

Climatic proofing  
Damp heat, constant, to IEC 60068-2-78  
Damp heat, cyclic, to IEC 60068-2-30

Ambient temperature  
Ambient temperature, storage  
- 40 - + 70 °C

Ambient temperature  
Operation  
-25 - +70 °C


Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27  
15 (half-sinusoidal shock 11 ms) g

Safe isolation to EN 61140  
Between auxiliary contacts and main contacts  
500 V AC

Safe isolation to EN 61140  
between the auxiliary contacts  
300 V AC

#### Mounting position

Vertical and 90° in all directions



With XFI earth-fault release:

- NZM1, N1, NZM2, N2: vertical  
and 90° in all directions

with plug-in unit

- NZM1, N1, NZM2, N2:  
vertical, 90° right/left

with withdraw able unit:

- NZM3, N3: vertical, 90°  
right/left

- NZM4, N4: vertical

with remote operator:

- NZM2, N(S)2, NZM3, N(S)3,  
NZM4, N(S)4: vertical and 90°  
in all directions

Direction of incoming supply  
as required

Degree of protection

Device

In the operating controls area: IP20 (basic degree  
of protection)

Degree of protection

Enclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protection

Terminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)  
Temperature dependency, Derating

## Circuit-breakers

Rated current = rated uninterrupted current [ $I_n = I_u$ ]  
550 A

Rated surge voltage invariability [ $U_{imp}$ ]  
Main contacts  
8000 V

Rated surge voltage invariability [ $U_{imp}$ ]  
Auxiliary contacts  
6000 V

Rated operational voltage [ $U_e$ ]  
690 V AC

Overvoltage category/pollution degree  
III/3

Rated insulation voltage [ $U_i$ ]  
1000 V

Use in unearthed supply systems  
 525 V

## Switching capacity

Rated short-circuit making capacity [ $I_{cm}$ ]  
240 V [ $I_{cm}$ ]  
105 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
400/415 V [ $I_{cm}$ ]  
105 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
440 V 50/60 Hz [ $I_{cm}$ ]  
74 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
525 V 50/60 Hz [ $I_{cm}$ ]

53 kA

Rated short-circuit making capacity [ $I_{cm}$ ]  
690 V 50/60 Hz [ $I_c$ ]  
40 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
240 V 50/60 Hz [ $I_{cu}$ ]  
50 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
400/415 V 50/60 Hz [ $I_{cu}$ ]  
50 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
440 V 50/60 Hz [ $I_{cu}$ ]  
35 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
525 V 50/60 Hz [ $I_{cu}$ ]  
25 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cu}$  to IEC/EN 60947 test cycle O-t-OO [ $I_{cu}$ ]  
690 V 50/60 Hz [ $I_{cu}$ ]  
20 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ]  
240 V 50/60 Hz [ $I_{cs}$ ]  
37 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ]  
400/415 V 50/60 Hz [ $I_{cs}$ ]  
37 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ]  
440 V 50/60 Hz [ $I_{cs}$ ]  
26 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 $I_{cs}$  to IEC/EN 60947 test cycle O-t-OO-t-OO [ $I_{cs}$ ]  
525 V 50/60 Hz [ $I_{cs}$ ]  
19 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [Ics]  
690 V 50/60 Hz [ $I_{cs}$ ]  
15 kA

Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.

Rated short-time withstand current  
 $t = 0.3$  s [ $I_{cw}$ ]  
19.2 kA

Rated short-time withstand current  
 $t = 1$  s [ $I_{cw}$ ]  
19.2 kA

Utilization category to IEC/EN 60947-2  
B

Lifespan, mechanical (of which max. 50 % trip by shunt/undervoltage release) [Operations]  
10000

Lifespan, electrical  
AC-1  
400 V 50/60 Hz [Operations]  
3000

Lifespan, electrical  
AC-1  
415 V 50/60 Hz [Operations]  
3000

Lifespan, electrical  
AC-1  
690 V 50/60 Hz [Operations]  
2000

Lifespan, electrical  
AC-3  
400 V 50/60 Hz [Operations]  
2000

Lifespan, electrical  
AC-3  
415 V 50/60 Hz [Operations]

2000

Lifespan, electrical  
AC-3  
690 V 50/60 Hz [Operations]  
1000

Lifespan, electrical  
Max. operating frequency  
60 Ops/h

Total break time at short-circuit  
< 25 □ 415 V; < 35 > 415 V ms

## Terminal capacity

Standard equipment  
Screw connection

Optional accessories  
Tunnel terminal  
connection on rear  
Strip terminal

Round copper conductor  
Tunnel terminal  
Stranded  
4-hole  
4 x (50 - 240) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Direct on the switch  
Stranded  
1 x (120 - 185)  
4 x (50 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [min.]  
1 x (120 - 300) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (95 - 300) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole [min.]  
2 x (95 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole [max.]  
4 x (35 - 185) mm<sup>2</sup>

Round copper conductor  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension  
4 x 300  
6 x (95 - 240) mm<sup>2</sup>

Al circular conductor  
Tunnel terminal  
Stranded  
4-hole  
4 x (50 - 240) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [min.]  
1 x (185 - 240) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (70 - 185) mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Module plate  
Double hole  
4 x 50 mm<sup>2</sup>

Al circular conductor  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension  
2 x 240  
6 x (70 - 240) mm<sup>2</sup>

Cu strip (number of segments x width x segment  
thickness)  
Flat conductor terminal [min.]

6 x 16 x 0.8 mm

Cu strip (number of segments x width x segment thickness)  
Flat conductor terminal [max.]  
(2 x) 10 x 32 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Module plate  
Single hole  
(2 x) 10 x 50 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Bolt terminal and rear-side connection  
Flat copper strip, with holes [min.]  
5 x 25 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Bolt terminal and rear-side connection  
Flat copper strip, with holes [max.]  
(2 x) 10 x 50 x 1.0 mm

Cu strip (number of segments x width x segment thickness)  
Bolt terminal and rear-side connection  
Connection width extension  
(2 x) 10 x 80 x 1.0 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Screw connection  
M10

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Direct on the switch [min.]  
25 x 5 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Direct on the switch [max.]  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Single hole [min.]  
25 x 5 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Single hole [max.]  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Module plate  
Double hole  
2 x (50 x 10) mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension [min.]  
60 x 10 mm

Copper busbar (width x thickness) [mm]  
Bolt terminal and rear-side connection  
Connection width extension  
Connection width extension [max.]  
2 x (80 x 10) mm

Control cables  
1 x (0.75 - 2.5)  
2 x (0.75 - 1.5) mm<sup>2</sup>

## DESIGN VERIFICATION AS PER IEC/EN 61439

### Technical data for design verification

Rated operational current for specified heat  
dissipation [ $I_n$ ]  
550 A

Equipment heat dissipation, current-dependent  
[ $P_{id}$ ]  
33.58 W

Operating ambient temperature min.  
-25 °C

Operating ambient temperature max.  
+70 °C

## IEC/EN 61439 design verification

10.2 Strength of materials and parts  
10.2.2 Corrosion resistance  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.1 Verification of thermal stability of enclosures  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts  
10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts  
10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties  
10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

# TECHNICAL DATA ETIM 7.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC000074)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ecl@ss10.0.1-27-37-04-01 [AGZ529016])

Overload release current setting  
275 - 550 A

Adjustment range undelayed short-circuit release  
550 - 7700 A

With thermal protection  
Yes

Phase failure sensitive  
Yes

Switch off technique  
Electronic

Rated operating voltage  
690 - 690 V

Rated permanent current I<sub>u</sub>  
550 A

Rated operation power at AC-3, 230 V  
160 kW

Rated operation power at AC-3, 400 V  
315 kW

Type of electrical connection of main circuit  
Screw connection

Type of control element  
Rocker lever

Device construction  
Built-in device fixed built-in technique

With integrated auxiliary switch  
No

With integrated under voltage release  
No

Number of poles  
3

Rated short-circuit breaking capacity  $I_{cu}$  at 400 V,  
AC  
50 kA

Degree of protection (IP)  
IP20


Height  
207 mm

Width  
210 mm


Depth  
401 mm

## CHARACTERISTICS

Characteristic curve



## DIMENSIONS



- Blow out area, minimum clearance to adjacent parts
  - $U_i \leq 690 \text{ V}$ : 100 mm
  - $U_i \leq 1500 \text{ V}$ : 200 mm
- Minimum clearance to adjacent parts
  - $U_i \leq 1000 \text{ V}$ : 15 mm
  - $U_i \leq 1500 \text{ V}$ : 70 mm

