



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZM3-XHB - Main switch assembly kit, handle black, size 3



266628 NZM3-XHB

[Overview](#) [Specifications](#) [Resources](#)

266628 NZM3-XHB

Main switch assembly kit, handle black, size 3

EL-Nummer (Norway)

4315577

Optional accessories for circuit-breaker series NZM offers a comprehensive portfolio of application possibilities for worldwide use. Modular functional groups make mounting flexible and simple. Note: Door coupling rotary handle with rotary drive. Extension shaft NZM.-XV4. External warning plate/marking plate in German/English, black and yellow flash. External warning plate/marking plate can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. With black door coupling rotary handle. Lockable on the 0 position on the handle using up to 3 padlocks, can also be modified in 1 position. With door interlock. Can be used for: NZM(-4), PN3(-4), N(VO)3(-4)

- [Delivery program](#)

Design verification as per
IEC/EN 61439

- [Technical data ETIM 7.0](#)

- [Approvals](#)

- [Dimensions](#)

Delivery program

Equipment supplied

Door coupling rotary handle with rotary drive

NZM..-XV4 extension shaft

External warning plate/marking plate in German/English

Black and yellow lightning symbol

Product range

Accessories

Accessories

Main switch assembly kit

Standard/Approval

UL/CSA, IEC

Construction size

NZM3

Description

Kit for use as a main switch

Function

With black door coupling rotary handle

Protection class

IP66

UL/CSA Type 4X, Type 12

Locking facility

lockable on the 0 position on the handle using up to 3 padlocks

can also be modified in 1 position

With door interlock

Door interlock

Door interlock on OFF with max. 3 padlocks

can also be modified in 1 position

After the door interlock is activated, must not be opened while on ON or TRIP. Must only be opened on OFF

Can be modified such that it can be defeated from the outside using a screw driver
Not defeated in the locked OFF position.
Can only be switched ON when the door is closed
Project planning information
External warning plate/designation label can be clipped on.
For enhanced busbar tag shroud on the incomming side, please order IP2X protection against contact with a finger.
For use with
NZMB(-4)
PNB(-4), NS(S)3(-4)

Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0


Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EO000229)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss10.0.1-27-37-04-14 [AKF012014])
Lockable
Yes
Colour
Black
Suitable for emergency stop
No
With extension shaft

Yes
Suitable for power circuit breaker
Yes
Suitable for switch disconnector
Yes

Approvals

Product Standards
UL489; CSA-C22.2 No. 5-09; IEC60947, CE marking
UL File No.
E140305
UL Category Control No.
DIHS
CSA File No.
022086
CSA Class No.
1437-01
North America Certification
UL listed, CSA certified
Degree of Protection
IEC: IP66, UL/CSA Type 4X, 12

Dimensions



Minimum door coupling rotary handle clearance from door pivot point

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)


DWG files

- [DA-CD-nzm3_xhb](#)
File
(Web)

Step files

- [DA-CS-nzm3_xhb](#)
File
(Web)


Dimensions single product



[123X369](#)

Line drawing

Mechanical interlock, door coupling rotary handle




[123X489](#)

Line drawing

Minimum door coupling rotary handle clearance from door pivot point

3D drawing



1231676

Line drawing

Main switch assembly kit

Product photo



1230PIC-739

Photo

Instruction Leaflet

- [NZM1,2 XTV DKL \(IL01203005Z\)](#)

Asset

IL01203005Z

(PDF, 03/21, Language independent)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal](#) [Disclaimer](#) [Terms and Conditions](#)

©2022 by Eaton Industries GmbH