

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



IZMX16N3-V12W-1 - Circuit-breaker, 3 pole, 1250A, 50 kA, Selective operation, IEC, Withdraw able



183349 IZMX16N3-V12W-1

[Overview](#) [Specifications](#) [Resources](#)



- [Delivery program](#)
- [Technical data](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

183349 IZMX16N3-V12W-1

Circuit-breaker, 3 pole, 1250A, 50 kA, Selective operation, IEC, Withdraw able
EL-Nummer (Norway) 4398023

Circuit-breaker IZMX16 (Air circuit-breakers/switch-disconnectors), 3 pole, Current Range: Up to 4000 A, Rated current = rated uninterrupted current($I_n = I_u$): 1250 A, up to 440 V 50/60 Hz(I_{cu}): 50 kA, up to 440 V 50/60 Hz(I_{cs}): 50 kA, Overload release, min.(I_r): 500 A, Overload release, max.(I_r): 1250 A, Installation type: Withdraw able, Standard/Approval: IEC, Protective function: Selective operation


Delivery program

Product range
Air circuit-breakers/switch-disconnectors
Product range
Open circuit-breakers
Current Range
Up to 4000 A
Protective function
Selective operation
Installation type
Withdrawable
Cassette must be separately ordered.
Main terminals must be separately ordered.
Construction size
IZMX16
Release system
Electronic release
Standard/Approval
IEC
Number of poles
3 pole
Degree of Protection
IP31 with door seals, IP55 with protective cover
suitable for zone selectivity
optionally fittable by user with comprehensive accessories
Rated current = rated uninterrupted current [$I_n = I_u$]

1250 A
 up to 440 V 50/60 Hz [I_{cu}]
 50 kA
 up to 440 V 50/60 Hz [I_{cs}]
 50 kA
 Overload release, min. [I_r]
 500 A
 Overload release, max. [I_r]
 1250 A
 Non-delayed  [$I_t = I_n \times \dots$]
 2 - 15, OFF
 Delayed  [$I_{sd} = I_r \times \dots$]
 1,5 - 10

Technical data

General
 Standards
 IEC/EN 60947
 Ambient temperatureStorage [9]
 -20 - +70 °C
 Ambient temperatureAmbient temperature
 -20 - +70 °C
 Mounting position



Utilization category
 B
 Degree of Protection
 IP31 with door seals, IP55 with protective cover
 Direction of incoming supply
 as required
 Main conducting paths
 Rated current = rated uninterrupted current [$I_n = I_u$]
 1250 A
 Rated uninterrupted current at 50 °C [I_u]
 1250 A
 Rated uninterrupted current at 60 °C [I_u]
 1250 A
 Rated uninterrupted current at 70 °C [I_u]
 1250 A
 Rated impulse withstand voltage [U_{imp}]
 12000 V AC
 Rated operational voltage [U_e]
 690 V AC
 Use in IT electrical power networks up to [U]
 440 V
 Overvoltage category/pollution degree
 III/3
 Rated insulation voltage [U_i]
 1000 V
 Switching capacity
 Rated short-circuit making capacity [I_{cm}] up to 440 V 50/60 Hz [I_{cm}]
 105 kA
 Rated short-circuit making capacity [I_{cm}] up to 690 V 50/60 Hz [I_{cm}]
 88 kA
 Rated short-time withstand current 50/60 Hz $t = 1$ s [I_{cw}]
 42 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] IEC/EN 60947 operating sequence I_{cu} O-t-CO up to 240 V 50/60 Hz [I_{cu}]
 85 kA
 Rated short-circuit breaking capacity I_{cn} [I_{cn}] IEC/EN 60947 operating sequence I_{cu} O-t-CO up to 440 V 50/60 Hz [I_{cu}]
 50 kA

Rated short-circuit breaking capacity I_{cn} [kA] IEC/EN 60947 operating sequence I_{cu} O-t-COup to 690 V 50/60 Hz [I_{cu}] 42 kA

Rated short-circuit breaking capacity I_{cn} [kA] IEC/EN 60947 operating sequence I_{cs} O-t-CO-t-COup to 240 V 50/60 Hz [I_{cs}] 50 kA

Rated short-circuit breaking capacity I_{cn} [kA] IEC/EN 60947 operating sequence I_{cs} O-t-CO-t-COup to 440 V 50/60 Hz [I_{cs}] 50 kA

Rated short-circuit breaking capacity I_{cn} [kA] IEC/EN 60947 operating sequence I_{cs} O-t-CO-t-COup to 690 V 50/60 Hz [I_{cs}] 42 kA

Operating times Closing delay via spring release 30 ms

Operating times Total opening delay via shunt release 30 ms

Operating times Total opening delay via undervoltage release 50 ms

Operating times Total opening delay on non-delayed short-circuit release (up to complete arc quenching) 27 ms

Lifespan Lifespan, mechanical [Switching cycles (ON/OFF)] 12500

Lifespan Lifespan, mechanical with maintenance [Switching cycles (ON/OFF)] 25000.

Lifespan Lifespan, electrical [Switching cycles (ON/OFF)] 10000

Lifespan Lifespan, electrical with maintenance [Switching cycles (ON/OFF)] 20000.

Maximum operating frequency [Operations/h] 60

Heat dissipation at rated current I_n Withdrawable units (switch with cassette) 180 W

Weight

Withdrawable 3-pole 28 kg

Cassette 3 pole 18 kg

Terminal capacities

Copper bar Withdrawable units Black 2 x 5 x 80 mm

These are values used in separate switchgear. The actual values will depend on the temperature around the circuit-breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the partitions, and any external ventilation. Depending on the specific switchgear design, this may result in derating, which can then be compensated for by increasing the cross-sectional area. Temperature rise tests in the specific switchgear can provide specific and detailed information.

Permissible continuous current for circuit-breakers operating in switchboards at various internal ambient temperatures. The switchboard's internal ambient temperature should be estimated using the calculation methods of IEC regulation.

Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I_n]

1250 A

Equipment heat dissipation, current-dependent [P_{ed}]

180 W

Operating ambient temperature min.

-20 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances
Meets the product standard's requirements.

10.5 Protection against electric shock
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections
Is the panel builder's responsibility.

10.8 Connections for external conductors
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material
Is the panel builder's responsibility.

10.10 Temperature rise
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EG000228)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current I_n
1250 A

Rated voltage
690 - 690 V

Rated short-circuit breaking capacity I_{cu} at 400 V, 50 Hz
50 kA

Overload release current setting
500 - 1250 A

Adjustment range short-term delayed short-circuit release
750 - 12500 A

Adjustment range undelayed short-circuit release
2500 - 18750 A

Integrated earth fault protection
No

Type of electrical connection of main circuit
Rail connection

Device construction
Built-in device slide-in technique (withdrawable)

Suitable for DIN rail (top hat rail) mounting
No


DIN rail (top hat rail) mounting optional
No

Number of auxiliary contacts as normally closed contact
0

Number of auxiliary contacts as normally open contact
0

Number of auxiliary contacts as change-over contact
2
With switched-off indicator
Yes
With under voltage release
No
Number of poles
3
Position of connection for main current circuit
Back side
Type of control element
Push button
Complete device with protection unit
Yes
Motor drive integrated
No
Motor drive optional
Yes
Degree of protection (IP)
IP31

Dimensions



- ☐ Door
- ☐ Contact surface flange terminal

CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-izmx16_3pol_w](#)
File
(Web)

edz files

- [DA-CE-ETN.IZMX16N3-V12W-1](#)
File
(Web)

Step files

- [DA-CS-izmx16_3pol_w](#)
File
(Web)


Product photo



[sg05216](#)

Photo
IZMX16B, 3 pole, withdraw able units


Dimensions single product



[1230DIM-384](#)

Line drawing


- ☐ Door
- ☐ Contact surface flange terminal



[123N098](#)

Line drawing

Mounting position



[123N099](#)

Line drawing

Mounting position

Tender text

- [Tender text ZMX16N3-V12W-1 \(TT-ZMX16N3-V12W-1-183349\)](#)
 (Microsoft Word, de)

Download-Center

- [Download-Center \(this item\)](#)
 Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
 Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

