



Switch-disconnector 4p + plug-in contacts

| | | |
|-----------------------|--------------|--|
| Part no. | N3-4-630-SVE | |
| Catalog No. | 168471 | |
| Alternate Catalog No. | N3-4-630-SVE | |
| EL-Nummer (Norway) | 4356983 | |


Similar to illustration

Delivery program

| | | | |
|------------------------------------------------------|-------------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description | | | Main switch characteristics including positive drive to IEC/EN 60204 and VDE 0113. Isolating characteristics to IEC/EN 60947-3 and VDE 0660. Busbar tag shroud to VDE 0160 Part 100. |
| Rated current = rated uninterrupted current | $I_n = I_u$ | A | 630 |
| Short-circuit protection max. fuse gL-characteristic | | A gL | 630 |

Technical data

General

| | | | |
|------------------------------|--|----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature | | | |
| Ambient temperature, storage | | °C | -40 - +70 |
| Operation | | °C | -25 - +70 |
| Mounting position | | | |
| Mounting position | | | Vertical and 90° in all directions  With residual-current release XFI: - NZM1, N1, NZM2, N2: vertical and 90° in all directions with plug-in adapter elements - NZM1, N1, NZM2, N2: vertical, 90° right/left with withdrawable unit: - NZM3, N3: vertical, 90° left - NZM4, N4: vertical with remote operator: - NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions |

Switch-disconnectors

| | | | |
|---------------------------------------------|-------------|---|-----|
| Rated current = rated uninterrupted current | $I_n = I_u$ | A | 630 |
| Rated making and breaking capacity | | | |
| Rated operational current | I_e | A | |
| AC-22/23A | | | |
| 415 V | I_e | A | 630 |
| 690 V | I_e | A | 630 |

Design verification as per IEC/EN 61439

| | | | |
|------------------------------------------------------------------------------------------------------------------------|-----------|----|--------------------------------------------------------------------|
| Technical data for design verification | | | |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 107.16 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |

| | |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 10.3 Degree of protection of ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | Is the panel builder's responsibility. |
| 10.9 Insulation properties | |
| 10.9.2 Power-frequency electric strength | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | Is the panel builder's responsibility. |
| 10.10 Temperature rise | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Switch disconnector (EC000216)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnector (ecl@ss10.0.1-27-37-14-03 [AKF060013])

| | |
|---------------------------------------------------------|-----------------------------------|
| Version as main switch | Yes |
| Version as maintenance-/service switch | Yes |
| Version as safety switch | No |
| Version as emergency stop installation | Yes |
| Version as reversing switch | No |
| Number of switches | 1 |
| Max. rated operation voltage Ue AC | V 690 |
| Rated operating voltage | V 690 - 690 |
| Rated permanent current Iu | A 630 |
| Rated permanent current at AC-23, 400 V | A 0 |
| Rated permanent current at AC-21, 400 V | A 0 |
| Rated operation power at AC-3, 400 V | kW 0 |
| Rated short-time withstand current Icw | kA 12 |
| Rated operation power at AC-23, 400 V | kW 315 |
| Switching power at 400 V | kW 0 |
| Conditioned rated short-circuit current Iq | kA 0 |
| Number of poles | 4 |
| Number of auxiliary contacts as normally closed contact | 0 |
| Number of auxiliary contacts as normally open contact | 0 |
| Number of auxiliary contacts as change-over contact | 0 |
| Motor drive optional | Yes |
| Motor drive integrated | No |
| Voltage release optional | Yes |
| Device construction | Built-in device plug-in technique |
| Suitable for ground mounting | Yes |
| Suitable for front mounting 4-hole | No |
| Suitable for front mounting centre | No |
| Suitable for distribution board installation | Yes |
| Suitable for intermediate mounting | Yes |
| Colour control element | Black |
| Type of control element | Rocker lever |
| Interlockable | Yes |
| Type of electrical connection of main circuit | Screw connection |
| Degree of protection (IP), front side | IP20 |

Additional product information (links)

additional technical information for NZM power switch

https://es-assets.eaton.com/DOCUMENTATION/PDF/nzm_technic_de_en.pdf