



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZMS3-VE400-SVE - Circuit-breaker, 3 p, 400A, plug-in module



168526 NZMS3-VE400-SVE

[Overview](#) [Specifications](#) [Resources](#)

## 168526 NZMS3-VE400-SVE

Circuit-breaker, 3 p, 400A, plug-in module

Alternate Catalog No.

NZMS3-VE400-SVE

EL-Nummer (Norway)

4357601

Series NZM.-VE circuit-breakers cover all application cases with just four compact sizes and are suitable for the IEC market. Modular function groups always make mounting flexible. With electronic actuators for systems and cable protection, selective and generator protection. Overload, briefly delayed, and non-delayed short-circuit protection. Notes: r.m.s. value measurement and thermal memory, adjustable time delay setting to overcome current peaks  $t_r$ : 2-14 s at  $6 \times I_r$  as well as infinity (without overload release), adjustable deceleration time  $t_{sd}$ : stages: 0, 1000 ms,  $i^2t$  constant function: switched

- Design verification as per IEC/EN 61439

- Technical data ETIM 7.0

### Design verification as per IEC/EN 61439

Technical data for design verification

Equipment heat dissipation, current-dependent [ $R_{id}$ ]

48 W

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EO000228)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss10.0.1-27-37-04-09 [AJZ716013])

Rated permanent current  $I_{cu}$   
400 A

Rated voltage  
690 - 690 V

Rated short-circuit breaking capacity  $I_{cu}$  at 400 V, 50 Hz  
65 kA

Overload release current setting  
200 - 400 A

Adjustment range short-term delayed short-circuit release  
400 - 4000 A

Adjustment range undelayed short-circuit release  
800 - 4400 A

Integrated earth fault protection  
No

Type of electrical connection of main circuit  
Screw connection

Device construction  
Built-in device plug-in technique

Suitable for DIN rail (top hat rail) mounting  
No

DIN rail (top hat rail) mounting optional  
No

Number of auxiliary contacts as normally closed contact  
0

Number of auxiliary contacts as normally open contact  
0

Number of auxiliary contacts as change-over contact  
0

With switched-off indicator  
No

With under voltage release  
No

Number of poles  
3

Position of connection for main current circuit  
Back side

Type of control element  
Rocker lever

Complete device with protection unit  
Yes  
Motor drive integrated  
No  
Motor drive optional  
Yes  
Degree of protection (IP)  
IP20

## CAD data

- [Product-specific CAD data \(Web\)](#)
- [3D Preview \(Web\)](#)

## DWG files

- [DA-CD-nzrh3\\_me220\\_sve](#)  
File  
(Web)

## edz files

- [DA-OE-ETN.NZMS3-VE400-SVE](#)  
File  
(Web)

## Step files

- [DA-CS-nzrh3\\_me220\\_sve](#)  
File  
(Web)

## Product photo



1230PIC-1324  
Photo

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH