



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZM4-4-XKV2P - Terminal jumper, with cover, 4p, /2p



119888 NZM4-4-XKV2P

[Overview](#) [Specifications](#) [Resources](#)

## 119888 NZM4-4-XKV2P

Terminal jumper, with cover, 4p, /2p

EL-Nummer (Norway)

4356085

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use worldwide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. contains parts for upper switch side for 4 pole switches N...-S1-DC that are used as 2 pole switches for DC. The links each connect 2 contacts in series. Incoming unit and outgoer at bottom or top, user-definable. = 1250A; for 65 °C ambient air temperature connection at bottom through module plates NZM4-4-XKM2S-1600. Use jumper kit with cover for: N4-4...S1-DC

- [Delivery program](#)
- [Design verification as per IEC/EN 61439](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

### Delivery program

Number of poles

2 pole

Accessories

DC link kit

Number of conductors

4

Jumper kit with cover IP2X

Rated current [I<sub>n</sub>]

1400 (40 °C,)

1260 (65 °C) A

For use with

N4-4...-S1(-S15)-DC

N4-4-800(1000)(1100)-S1(-S15)-PV-NA

#### Notes

Model contains parts for upper switch side for 4 pole switches N...-DC that are used as 2 pole switches for DC.

The links each connect contacts in series.

Incoming unit and outgoer at bottom or top, user-definable.

See figure connection type.

### Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts 10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.


10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Wiring set for power circuit breaker (EC002050)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Wiring set for circuit breaker (ecl@ss10.0.1-27-37-04-24 [ACN957011])  
Suitable for number of poles  
4  
Model  
Other

## Dimensions




## CAD data

- Product-specific CAD data (Web)
- 3D Preview (Web)

## Product photo



## 3D drawing




1230PIC-777

Line drawing

Terminal jumpers

## Dimensions single product



1230DIM-345

Line drawing

## Symbol

- **New**

0000SPC-173

Graphic

Logo new yellow small

## Instruction Leaflet

- [IL01210016Z](#)

Asset

(PDF, Language independent)

## Download-Center

- [Download-Center \(this item\)](#)

Eaton EMEA Download-Center - download data for this item

- [Download-Center](#)

Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#)
[Privacy Policy](#)
[Legal Disclaimer](#)
[Terms and Conditions](#)

© 2022 by Eaton Industries GrnbH