

Select your language

- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



NZM4-XKSAV - Cover, 3p, for connection width extension



119876 NZM4-XKSAV

[Overview](#) [Specifications](#) [Resources](#)



# 119876 NZM4-XKSAV

Cover, 3p, for connection width extension

EL-Nummer (Norway)

4359071

Optional accessories for the circuit-breaker series NZM offers a comprehensive portfolio of application options for use world wide. The mounting is always flexible and easy thanks to the modular function groups. Notes: part no. contains parts for a terminal located at top or bottom for 3 pole switches.

Insulation protection / busbar tag shroud for connection of cable lugs or busbars to connection width extension. When using insulated conductor material to IP2X. cannot be combined with connection width extension NZM4-XKV110. Can be used for: NZM4, N(S)4, NZM4-XKV95(KB)

- Delivery program

Design verification as per IEC/EN 61439

- Technical data ETIM 7.0

- Approvals

- Dimensions

## Delivery program

Accessories

Terminal cover

Number of conductors

3 pole

Accessories

Terminal cover

For use with

NZM4, N(S)4

+ NZM4-XKV95(KB)

### Notes

Type contains parts for a terminal located at top or bottom for 3 pole circuit-breakers.

Insulation protection/busbar tag shroud for connection of cable lugs or busbars to connection width extension.

When using insulated conductor material to IP2X.

Cannot be combined with connection width extension NZM4-XKV110.

## Design verification as per IEC/EN 61439

IEC/EN 61439 design verification

10.2 Strength of materials and parts10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
 Meets the product standard's requirements.  
 10.2 Strength of materials and parts 10.2.5 Lifting  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts 10.2.6 Mechanical impact  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.2 Strength of materials and parts 10.2.7 Inscriptions  
 Meets the product standard's requirements.  
 10.3 Degree of protection of ASSEMBLIES  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.4 Clearances and creepage distances  
 Meets the product standard's requirements.  
 10.5 Protection against electric shock  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.6 Incorporation of switching devices and components  
 Does not apply, since the entire switchgear needs to be evaluated.  
 10.7 Internal electrical circuits and connections  
 Is the panel builder's responsibility.  
 10.8 Connections for external conductors  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.2 Power-frequency electric strength  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.3 Impulse withstand voltage  
 Is the panel builder's responsibility.  
 10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
 Is the panel builder's responsibility.  
 10.10 Temperature rise  
 The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.  
 10.11 Short-circuit rating  
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.  
 10.12 Electromagnetic compatibility  
 Is the panel builder's responsibility. The specifications for the switchgear must be observed.  
 10.13 Mechanical function  
 The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.


## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Phase separation plate for power circuit breaker (EC002035)  
 Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Phase separation plate for circuit breaker (ec1@ss10.0.1-27-37-04-25 [ACN959011])  
 Model  
 Other

## Approvals

North America Certification  
 UL/CSA certification not required

## Dimensions



## CAD data

- [Product-specific CAD data](#)  
(Web)
- [3D Preview](#)  
(Web)

## DWG files

- [DA-CD-nzm4\\_xksav](#)  
File  
(Web)

## Step files

- [DA-CS-nzm4\\_xksav](#)  
File  
(Web)



## Product photo

-   
[1230PIC-699](#)  
Photo

## 3D drawing

-   
[1230DRV-734](#)  
Line drawing  
Shroud, large

## Dimensions single product

-   
[1230DIM-241](#)  
Line drawing  
Cover size
-   
[123X338](#)  
Line drawing  
Cover for screw terminals

## Symbol

- **New**  
[0000SPC-173](#)  
Graphic  
Logo new yellow small

## Instruction Leaflet

- [IL01210015Z](#)  
Asset  
(PDF, Language independent)

## Download-Center

- [Download-Center \(this item\)](#)  
Eaton EMEA Download-Center - download data for this item

- [Download-Center](#)  
Eaton EMEA Download-Center



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

