



- German
- English
- Spanish
- French
- Dutch
- Italian
- Polish
- Czech
- Russian
- Norwegian Bokmål

Worldwide English



Powering Business Worldwide

NZMN2-M125 - Circuit-breaker, 3p, 125A



265723 NZMN2-M125

[Overview](#) [Specifications](#) [Resources](#)

- Delivery program
- Technical data
- Design verification as per IEC/EN 61439
- Technical data ETIM 7.0
- Characteristics
- Dimensions

## 265723 NZMN2-M125

Circuit-breaker, 3p, 125A

EL-Nummer (Norway)

4315567

Circuit-breakers of the NZM.-Mseries cover all applications with only four compact sizes and are suitable for the IEC market. The mounting is always flexible due to the modular function groups. With thermomagnetic release for the motor protection. Notes: tripping class 10A, IEC/EN 60947-4-1, IEC/EN 60947-2 circuit-breakers fulfill all requirements of the switching category AC-3.

### Delivery program

Product range  
Circuit-breaker  
Protective function  
Motor protection




Standard/Approval  
IEC

Installation type  
Fixed  
Release system  
Thermomagnetic release  
Construction size  
NZM2  
Description  
Tripping class 10 A  
IEC/EN 60947-4-1, IEC/EN 60947-2

The circuit-breaker fulfills all requirements for AC-3 switching category.

Number of poles  
3 pole  
Standard equipment  
Screw connection

Switching capacity  
 400/415 V 50 Hz [ $I_{cu}$ ]  
 50 kA  
 Rated current = rated uninterrupted current [ $I_h = I_L$ ]  
 125 A  
**Setting range**  
 Overload trip  [ $I_r$ ]  
 100 - 125 A  
 Short-circuit releases  [ $I_{rm}$ ] Non-delayed  [ $I_r = I_h \times \dots$ ]  
 8 - 14  
 Motor rating AC-3 50/60 Hz [P]  
 380 V 400 V [P]  
 55 kW  
 Motor rating AC-3 50/60 Hz [P]  
 400 V [P]  
 55 kW  
 Rated operational current AC-3 50/60 Hz [ $I_e$ ]  
 400 V [ $I_e$ ]  
 99 A

## Technical data

### General

#### Standards

IEC/EN 60947

Protection against direct contact

Finger and back of hand proof to VDE 0106 Part 100

#### Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Ambient temperatureAmbient temperature, storage

-40 - +70 °C

Ambient temperatureOperation

-25 - +70 °C

Mechanical shock resistance (10 ms half-sinusoidal shock) according to IEC 60068-2-27

20 (half-sinusoidal shock 20 ms) g

Safe isolation to EN 61140 between auxiliary contacts and main contacts

500 V AC

Safe isolation to EN 61140 between the auxiliary contacts

300 V AC

#### Mounting position

Vertical and 90° in all directions
With XFI earth-fault release:
- NZM1, N1, NZM2, N2: vertical and 90° in all directions
with plug-in unit
- NZM1, N1, NZM2, N2: vertical, 90° right/left
with withdrawable unit:
- NZM3, N3: vertical, 90° right/left
- NZM4, N4: vertical
with remote operator:
- NZM2, N(S)2, NZM3, N(S)3, NZM4, N(S)4: vertical and 90° in all directions

Direction of incoming supply

as required

Degree of protectionDevice

In the operating controls area: IP20 (basic degree of protection)

Degree of protectionEnclosures

With insulating surround: IP40

With door coupling rotary handle: IP66

Degree of protectionTerminations

Tunnel terminal: IP10

Phase isolator and strip terminal: IP00

Other technical data (sheet catalogue)

[Temperature dependency, Derating](#)

Circuit-breakers

Rated current = rated uninterrupted current [ $I_h = I_L$ ]

125 A

Rated surge voltage invariability [ $U_{imp}$ ]Main contacts

8000 V  
 Rated surge voltage invariability [ $U_{imp}$ ]Auxiliary contacts  
 6000 V  
 Rated operational voltage [ $U_e$ ]  
 690 V AC  
 Overvoltage category/pollution degree  
 III/3  
 Rated insulation voltage [ $U_i$ ]  
 1000 V  
 Use in unearthed supply systems  
 □ 690 V  
 Switching capacity  
 Rated short-circuit making capacity [ $I_{cm}$ ]240 V [ $I_{cm}$ ]  
 187 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ]400/415 V [ $I_{cm}$ ]  
 105 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ]440 V 50/60 Hz [ $I_{cm}$ ]  
 74 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ]525 V 50/60 Hz [ $I_{cm}$ ]  
 53 kA  
 Rated short-circuit making capacity [ $I_{cm}$ ]690 V 50/60 Hz [ $I_c$ ]  
 40 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Icu to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ]240 V 50/60 Hz [ $I_{cu}$ ]  
 85 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Icu to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ]400/415 V 50/60 Hz [ $I_{cu}$ ]  
 50 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Icu to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ]440 V 50/60 Hz [ $I_{cu}$ ]  
 35 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Icu to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ]525 V 50/60 Hz [ $I_{cu}$ ]  
 25 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Icu to IEC/EN 60947 test cycle O-t-CO [ $I_{cu}$ ]690 V 50/60 Hz [ $I_{cu}$ ]  
 20 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ]240 V 50/60 Hz [ $I_{cs}$ ]  
 85 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ]400/415 V 50/60 Hz [ $I_{cs}$ ]  
 50 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ]440 V 50/60 Hz [ $I_{cs}$ ]  
 35 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ]525 V 50/60 Hz [ $I_{cs}$ ]  
 25 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]Ics to IEC/EN 60947 test cycle O-t-CO-t-CO [ $I_{cs}$ ]690 V 50/60 Hz [ $I_{cs}$ ]  
 5 kA  
 Rated short-circuit breaking capacity  $I_{cn}$  [ $I_{cn}$ ]  
 Maximum back-up fuse, if the expected short-circuit currents at the installation location exceed the switching capacity of the circuit-breaker.  
 Rated short-time withstand currentt = 0.3 s [ $I_{cw}$ ]  
 1.9 kA  
 Rated short-time withstand currentt = 1 s [ $I_{cw}$ ]  
 1.9 kA  
 Utilization category to IEC/EN 60947-2  
 A  
 Lifespan, mechanical(of which max. 50 % trip by shunt/undervoltage release) [Operations]  
 20000  
 Lifespan, electricalAC-1400 V 50/60 Hz [Operations]  
 10000  
 Lifespan, electricalAC-1415 V 50/60 Hz [Operations]  
 10000  
 Lifespan, electricalAC-1690 V 50/60 Hz [Operations]  
 7500  
 Lifespan, electricalAC-3400 V 50/60 Hz [Operations]  
 6500  
 Lifespan, electricalAC-3415 V 50/60 Hz [Operations]  
 6500  
 Lifespan, electricalAC-3690 V 50/60 Hz [Operations]  
 5000  
 Lifespan, electricalMax. operating frequency  
 120 Ops/h  
 Total break time at short-circuit  
 < 10 ms

**Terminal capacity**

Standard equipment

Screw connection

Optional accessories

Box terminal

Tunnel terminal

connection on rear

Round copper conductorBox terminalSolid

1 x (10 - 16)

2 x (6 - 16) mm<sup>2</sup>

Round copper conductorBox terminalStranded

1 x (25 - 185)

2 x (25 - 70) mm<sup>2</sup>

Round copper conductorTunnel terminalSolid

1 x 16 mm<sup>2</sup>

Round copper conductorTunnel terminalStranded1-hole

1 x (25 - 185) mm<sup>2</sup>

Round copper conductorBolt terminal and rear-side connectionDirect on the switchSolid

1 x (10 - 16)

2 x (6 - 16) mm<sup>2</sup>

Round copper conductorBolt terminal and rear-side connectionDirect on the switchStranded

1 x (25 - 185)

2 x (25 - 70) mm<sup>2</sup>

Al circular conductor Tunnel terminalSolid

1 x 16 mm<sup>2</sup>

Al circular conductor Tunnel terminalStrandedStranded

1 x (25 - 185) mm<sup>2</sup>

Al circular conductor Bolt terminal and rear-side connectionDirect on the switchSolid

1 x (10 - 16)

2 x (10 - 16) mm<sup>2</sup>

Al circular conductor Bolt terminal and rear-side connectionDirect on the switchStranded

1 x (25 - 50)

2 x (25 - 50) mm<sup>2</sup>

Cu strip (number of segments x width x segment thickness)Box terminal [min.]

2 x 9 x 0.8 mm

Cu strip (number of segments x width x segment thickness)Box terminal [max.]

10 x 16 x 0.8

(2x) 8 x 15.5 x 0.8 mm

Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip, with holes [min.]

2 x 16 x 0.8 mm

Cu strip (number of segments x width x segment thickness)Bolt terminal and rear-side connectionFlat copper strip, with holes [max.]

10 x 24 x 0.8 mm

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionScrew connection

M8

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [min.]

16 x 5 mm

Copper busbar (width x thickness) [mm]Bolt terminal and rear-side connectionDirect on the switch [max.]

24 x 8 mm

Control cables

1 x (0.75 - 2.5)

2 x (0.75 - 1.5) mm<sup>2</sup>

## Design verification as per IEC/EN 61439

Technical data for design verification

Rated operational current for specified heat dissipation [I<sub>h</sub>]

125 A

Equipment heat dissipation, current-dependent [P<sub>vid</sub>]

27.61 W

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

IEC/EN 61439 design verification

10.2 Strength of materials and parts10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.2 Verification of resistance of insulating materials to normal heat  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire  
due to internal electric effects

Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.4 Resistance to ultra-violet (UV) radiation  
Meets the product standard's requirements.

10.2 Strength of materials and parts 10.2.5 Lifting  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.6 Mechanical impact  
Does not apply, since the entire switchgear needs to be evaluated.

10.2 Strength of materials and parts 10.2.7 Inscriptions  
Meets the product standard's requirements.

10.3 Degree of protection of ASSEMBLIES  
Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances  
Meets the product standard's requirements.

10.5 Protection against electric shock  
Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components  
Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections  
Is the panel builder's responsibility.

10.8 Connections for external conductors  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.2 Power-frequency electric strength  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.3 Impulse withstand voltage  
Is the panel builder's responsibility.

10.9 Insulation properties 10.9.4 Testing of enclosures made of insulating material  
Is the panel builder's responsibility.

10.10 Temperature rise  
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility  
Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function  
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.


## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Motor protection circuit-breaker (EC0000074)  
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Motor protection circuit-breaker (ec1@ss10.0.1-27-37-04-01 [AGZ529016])  
Overload release current setting  
100 - 125 A  
Adjustment range undelayed short-circuit release  
1000 - 1750 A  
With thermal protection  
Yes  
Phase failure sensitive  
No  
Switch off technique  
Thermomagnetic  
Rated operating voltage  
690 - 690 V  
Rated permanent current I<sub>u</sub>  
125 A  
Rated operation power at AC-3, 230 V  
37 kW  
Rated operation power at AC-3, 400 V  
55 kW  
Type of electrical connection of main circuit  
Screw connection  
Type of control element  
Rocker lever


Device construction  
 Built-in device fixed built-in technique  
 With integrated auxiliary switch  
 No  
 With integrated under voltage release  
 No  
 Number of poles  
 3  
 Rated short-circuit breaking capacity  $I_{cu}$  at 400 V, AC  
 50 kA  
 Degree of protection (IP)  
 IP20  
 Height  
 184 mm  
 Width  
 105 mm  
 Depth  
 149 mm

## Characteristics

Characteristic curve




Characteristic curve




Let-through current

Characteristic curve



Let-through energy

## Dimensions



Blow out area, minimum clearance to adjacent parts

Minimum clearance to adjacent parts



## CAD data

- Product-specific CAD data  
(Web)
- 3D Preview  
(Web)

## DWG files

- DA-CD-nzm2\_3p  
File  
(Web)

## edz files

- DA-CE-ETN NZM2-M125

File

(Web)

## Step files

- DA-CS-nzm2\_3p


File

(Web)

## Additional product information

- Temperature dependency, Derating  
(Web)
- additional technical information for NZMpower switch  
(PDF)

## Dimensions single product




123X312

Line drawing

Circuit-breaker, switch-disconnector, 3-pole

- Blow out area, minimum clearance to adjacent parts
- Minimum clearance to adjacent parts



123X341

Line drawing

Circuit-breakers, switch-disconnectors


## Product photo



1230PIC-803

Photo

## Characteristic curve



1230DIA-55

Coordinate visualization


Let-through characteristics



1230DIA-6

Coordinate visualization

Let-through current



123U178

Coordinate visualization

NZM2-M125...200 tripping characteristic

## Tender text

- Tender text NZM2-M125 (TT-NZM2-M125)  
(Text)

## Standards



0000SPC-571

Logo

IE3-ready logo 4c  
(Int)

## Instruction Leaflet

- NZMB, NZMN (IL01206006Z)  
Asset  
(PDF, 11/2015, Language independent)

## Download-Center

- Download-Center (this item)  
Eaton EMEA Download-Center - download data for this item
- Download-Center  
Eaton EMEA Download-Center



Generate data sheet in PDF format



Generate data sheet in Excel format



Write a comment

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH