

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



IZMX-DC16-W-1 - Protective cover IP55. AV



184237 IZMX-DC16-W-1

[Overview](#) [Specifications](#) [Resources](#)



184237 IZMX-DC16-W-1

Protective cover IP55. AV

Alternate Catalog No.

68D2539G01

EL-Nummer (Norway)

4398580

Accessories, Protective cover, The front of the circuit-breaker projects through the door cut-out., The protective cover covers the circuit-breaker and the door cut-out and makes it possible to have an IP55 degree of protection., The protective cover can be swung open to the left or right., Installation type Withdrawable, For use with IZMX16...W, INX16...W

- [Delivery program](#)

Design verification as per
IEC/EN 61439

- [Technical data ETIM 7.0](#)

- [Dimensions](#)

Delivery program

Product range

Accessories

Accessories

Degree of protection IP55

Accessories

Protective cover

The front of the circuit-breaker projects through the door cut-out.

The protective cover covers the circuit-breaker and the door cut-out and makes it possible to have an IP55 degree of protection.

The protective cover can be swung open to the left or right.

For use with

IZMX16...W

INX16...W

Information about equipment supplied

The mounting kit includes a protective cover, a hinge, a door seal, and fixing material.

Installation type

Withdrawable

Design verification as per IEC/EN 61439

Operating ambient temperature min.

-25 °C

Operating ambient temperature max.

+70 °C

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])
Type of accessory
Cover

Technical drawing of the 'Cubo' lamp base. The drawing includes three views: a top view, a front view, and a side view. The top view shows a square base with a central square cutout. Dimensions are provided in centimeters: the outer square has a side length of 18.6 cm, and the inner square has a side length of 10.7 cm. The front view shows the base with a height of 10 cm. The side view shows the base with a depth of 10 cm. The base is made of a material with a thickness of 0.8 cm.


- Product-specific CAD data
(Web)
- 3D Preview
(Web)

- [DA-CD-izmx_dc_16_w](#)
File
(Web)


- [DA-OE-ETN.IZMX-DC16-W-1](#)
File
(Web)

- [DA-CS-izmx_dc_16_w](#)
File
(Web)

Dimensions single product



2/3



Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)
[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)
© 2022 by Eaton Industries GmbH