

Select your language

- [German](#)
- [English](#)
- [Spanish](#)
- [French](#)
- [Dutch](#)
- [Italian](#)
- [Polish](#)
- [Czech](#)
- [Russian](#)
- [Norwegian Bokmål](#)

Worldwide English



NZM1-XC43/2-TVDVR - Insulated enclosure, box size HxWxD=375x250x225mm, for NZMsize 1



104646 NZM1-XC43/2-TVDVR

[Overview](#) [Specifications](#) [Resources](#)



104646 NZM1-XC43/2-TVDVR

Insulated enclosure, box size HxWxD=375x250x225mm, for NZMsize 1

Insulated enclosure CI, degree of protection IP65, HxWxD=375x250x225mm, for NZMsize 1, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle red/yellow included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

- [Delivery program](#)
- [Technical data ETIM 7.0](#)
- [Dimensions](#)

Delivery program

Product range

xEnergy Safety CI

Accessories

Prepared enclosures

Description

With door coupling rotary handle

Complete with all required functional parts

Function

Red-yellow for emergency switching off

Locking facility

Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock.

Accessories

Accessories, others

Number of poles

3/4 pole

Standard/Approval

IEC

Construction size

NZM1

Degree of Protection

IP65

Rated uninterrupted current I_n at max. cross-section [I_n]

☐ ☐ 160 A A

Basic enclosure

C43-200

Terminal for retrofitting of 5th conductor (neutral conductor)

K50/1, K95/1N/BR

For use with

NZM1(-4), FN1(-4), N(S)1(-4)

Notes

Suitable for installation of circuit-breakers and switch-disconnectors Enclosure for separate mounting with top and bottom cable entry.

Include fixing straps for wall mounting.

Cannot be used in combination with NZM...XR... remote operator...

NZM...XSV plug-in unit or NZM...XAV withdrawable unit.

Insulated additional terminal for 4th or 5th pole should be ordered separately.

C1-K5 enclosure with hard metric knock-outs

C123 enclosure with flanges

C143, C145 and C148 feature gland plates.

Only for switches with box terminal for direct connection of cables.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Empty enclosure for switchgear (EC000712)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Empty housing for switch devices (ec1@ss10.0.1-27-37-13-01 [AKN343014])

Material housing

Plastic

Width

250 mm

Height

375 mm

Depth

225 mm

With transparent cover

Yes

Suitable for emergency stop

Yes

Model

Surface mounting


Degree of protection (IP)

IP65

Degree of protection (NEVA)

Other

Dimensions



CAD data

- [Product-specific CAD data](#)
(Web)
- [3D Preview](#)
(Web)

DWG files

- [DA-CD-nzm1_xci23_tvdvr](#)
File
(Web)
- [DA-CD-nzm1_xci43_2_tvdvr](#)
File
(Web)


Step files

- [DA-CS-nzm1_xci23_tvdvr](#)
File
(Web)
- [DA-CS-nzm1_xci43_2_tvdvr](#)
File
(Web)


Product photo

- 
[vt20417](#)
Photo
Insulated enclosure

3D drawing

- 
[4601054](#)
Line drawing
Insulated enclosure with door coupling rotary handle

Dimensions single product

- 
[1230DIM-51](#)
Line drawing
Insulated enclosure

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)
Eaton EMEA Download-Center

 [Generate data sheet in PDF format](#)

 [Generate data sheet in Excel format](#)

 [Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

