

< **HLR SOLID STATE RELAYS**
360047


Overview


Specifications


Resources

Questions be

General specifications	>
Features & Functions	>
General	>
Climatic environmental conditions	>
Electromagnetic compatibility	>
Terminal capacities	>
Electrical rating	>
Short-circuit rating	>
Control circuit	>
Motor rating	>
Design verification	>

GENERAL SPECIFICATIONS

PRODUCT NAME	Eaton Moeller series HLR solid state relay
CATALOG NUMBER	360047
MODEL CODE	HLR20/3(AC)600V
EAN	4015081998142
PRODUCT LENGTH/DEPTH	103 mm
PRODUCT HEIGHT	110 mm
PRODUCT WIDTH	54 mm
PRODUCT WEIGHT	.505 kg
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	CE UL 508 EAC CCC

MODEL CODE	HLR20/3(AC)600V
------------	-----------------

FEATURES & FUNCTIONS

FEATURES	Modular version
----------	-----------------

FUNCTIONS	Switching at zero-crossing
-----------	----------------------------

ELECTRICAL CONNECTION TYPE FOR AUXILIARY- AND CONTROL-CURRENT CIRCUIT	Screw connection
---	------------------

ELECTRICAL CONNECTION TYPE OF MAIN CIRCUIT	Screw connection
---	------------------

GENERAL

DEGREE OF PROTECTION	IP20
----------------------	------

FREQUENCY RATING	45 Hz - 65 Hz
------------------	---------------

MOUNTING POSITION	Mount device in specified orientation and do not heatsink
-------------------	--

NUMBER OF PHASES	3
------------------	---

NUMBER OF PILOT LIGHTS	1
------------------------	---

OVERVOLTAGE CATEGORY	III
----------------------	-----

POLLUTION DEGREE	2
------------------	---

RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6 kV (1.2/50 µs)
---	------------------

SERIES	HLR
SHOCK RESISTANCE	15/11 g/ms (according to EN 50155, EN 61373)
TYPE	Solid-state relay
VIBRATION RESISTANCE	2 g/axis (2-100 Hz, IEC 60068-2-6, EN 50155, EN 61373)
VOLTAGE TYPE	AC/DC

CLIMATIC ENVIRONMENTAL CONDITIONS

ALTITUDE	0 - 1000 m (Above 1000 m derate linearly by 1 % per 100 m up to a maximum of 2000 m)
AMBIENT STORAGE TEMPERATURE - MIN	-40 °C
AMBIENT STORAGE TEMPERATURE - MAX	100 °C
CLIMATIC PROOFING	95% relative humidity non-condensing at 40°C
OPERATING TEMPERATURE - MIN	-40 °C
OPERATING TEMPERATURE - MAX	80 °C

ELECTROMAGNETIC COMPATIBILITY

AIR DISCHARGE	8 kV (according to IEC/EN 61000-4-2)
BURST IMPULSE	Main: 2 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-2) Control: 1 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-2)
CONTACT DISCHARGE	4 kV (according to IEC/EN 61000-4-2)

ELECTROMAGNETIC FIELDS	10 V/m, 80 - 1000 MHz and 1.4 - 2.0 GHz, PC 1 (according to IEC/EN 61000-4-3) 10 V/m, 2.0 - 2.7 GHz, PC 1 (according to IEC/EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V/m, 0.15 - 80 MHz, PC 1 (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class A

TERMINAL CAPACITIES

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	Main: 1 x 1-4 mm ² , 2 x 1-4 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
TERMINAL CAPACITY (SOLID)	Main: 1 x 2.5-6 mm ² , 2 x 2.5-6 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
TERMINAL CAPACITY (SOLID/STRANDED AWG)	Main: 1 x 14-10, 2 x 14-10 Control: 1 x 18-12, 2 x 18-12
TERMINAL CAPACITY (STRANDED)	Main: 1 x 2.5-6 mm ² , 2 x 2.5-6 mm ² Control: 1 x 0.5-2.5 mm ² , 2 x 0.5-2.5 mm ²
TIGHTENING TORQUE	Main: 2 Nm (17.7 lb-in) Control: 0.5 Nm (4.4 lb-in)
SCREWDRIVER SIZE	Main: Pozidriv 2 Control: Pozidriv 1

ELECTRICAL RATING

OPERATING VOLTAGE - MAX.	660 V
OPERATING VOLTAGE - MIN.	42 V
RATED OPERATIONAL CURRENT (IE) AT AC-1	0 A

RATED OPERATIONAL CURRENT (IE) AT AC-3	0 A
---	-----

RATED OPERATIONAL CURRENT (IE) AT AC-51	20 A
--	------

RATED OPERATIONAL CURRENT (IE) AT AC-53A	10 A
---	------

RATED OPERATIONAL CURRENT (IE) AT AC-53B	0 A
---	-----

RATED OPERATIONAL VOLTAGE (UE) AT AC - MIN	42 V
---	------

RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	660 V
---	-------

SHORT-CIRCUIT RATING

RATED CONDITIONAL SHORT-CIRCUIT CURRENT, TYPE 1, 600 Y/347 V	100 kA
---	--------

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ), TYPE 2, 230 V	100 kA
--	--------

RATED CONDITIONAL SHORT-CIRCUIT CURRENT (IQ), TYPE 2, 380 V, 400 V, 415 V	100 kA
--	--------

CONTROL CIRCUIT

DELAY TIME	2 periods at 230 V AC
-------------------	-----------------------

DROP-OUT TIME	< 40 ms
----------------------	---------

DROP-OUT VOLTAGE	5 V AC
-------------------------	--------

INPUT CURRENT	18 mA at 230 V AC
---------------	-------------------

PICK-UP VOLTAGE	20 V AC
-----------------	---------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	20 V
---	------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	275 V
---	-------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	20 V
---	------

RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	275 V
---	-------

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
--	------

RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	190 V
--	-------

MOTOR RATING

HORSEPOWER	3 HP (230 V), 7.5 HP (480 V), 10 HP (600 V)
------------	---

RATED OPERATIONAL POWER AT 220/230 V, 50 HZ	2.2 kW
--	--------

RATED OPERATIONAL POWER AT 400 V, 50 HZ	4 kW
--	------

DESIGN VERIFICATION

EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	58 W
--	------

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	19.3 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	20 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Please enquire
10.2.5 LIFTING	Does not apply, since the entire switchgear need not be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear need not be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear need not be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear need not be evaluated.
10.6 INCORPORATION OF SWITCHING	Does not apply, since the entire switchgear need not be evaluated.

DEVICES AND COMPONENTS

evaluated.

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS

Is the panel builder's responsibility.

10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS

Is the panel builder's responsibility.

10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH

Is the panel builder's responsibility.

10.9.3 IMPULSE WITHSTAND VOLTAGE

Is the panel builder's responsibility.

10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL

Is the panel builder's responsibility.

10.10 TEMPERATURE RISE

The panel builder is responsible for the temperature calculation. Eaton will provide heat dissipation devices.

10.11 SHORT-CIRCUIT RATING

Is the panel builder's responsibility. The specifications for switchgear must be observed.

10.12 ELECTROMAGNETIC COMPATIBILITY


Is the panel builder's responsibility. The specifications for switchgear must be observed.

10.13 MECHANICAL FUNCTION

The device meets the requirements, provided that the conditions in the instruction leaflet (IL) is observed.

Resources >

How to buy from Eaton



Questions before you buy

Contact us via web form by clicking the link

above, or call us: +44 (0) 1753 608 700 option 2,
then option 1

[HLR solid state relays](#) > 360047