

|  |   |  |  |
|--|---|--|--|
| <b>360055</b>                            |   | <b>Eaton Moeller series HLR Solid-state relay, Hockey Puck, 1-phase, 100 A, 42 - 660 V, DC, high fuse protection</b>   |  |
| <b>General specifications</b>            | Product Name  | Eaton Moeller series HLR solid state relay   |  |
|  | Catalog Number  | 360055   |  |
|  | Model Code  | HLR100/1H(DC)600V/S  |  |
|  | EAN   | 4,01508E+12  |  |
|  | Product Length/Depth  | 28.8 mm  |  |
|  | Product Height  | 58.2 mm  |  |
|  | Product Width   | 44.8 mm  |  |
|  | Product Weight  | 0.1 kg   |  |
|  | Compliances   | CE Marked RoHS Compliant   |  |
|  | Certifications  | CE UL 508 EAC CCC  |  |
| <b>Features &amp; Functions</b>          | Functions   | Switching at zero-crossing   |  |
|  | Electrical connection type for auxiliary- and control-current circuit | Screw connection   |  |
|  | Electrical connection type of main circuit                            |  |  |
| <b>General</b>                           | Degree of protection  | IP20   |  |
|  | Frequency rating  | 45 Hz - 65 Hz  |  |
|  | Mounting position   | Mount device in specified orientation and do not obstruct the heatsink   |  |
|  | Number of phases  | 1  |  |
|  | Number of pilot lights  |  |  |
|  | Overvoltage category  | III  |  |
|  | Pollution degree  | 2  |  |
|  | Rated impulse withstand voltage (Uimp)                                | 6 kV (1.2/50 µs)   |  |
|  | Series  | HLR  |  |
|  | Shock resistance  | 15/11 g/ms (according to EN 50155, EN 61373)   |  |
|  | Type  | Solid-state relay  |  |
|  | Vibration resistance  | 2 g/axis (2-100 Hz, IEC 60068-2-6, EN 50155, EN 61373)   |  |
|  | Voltage type  | DC   |  |
|  | Altitude  | 0 - 1000 m (Above 1000 m derate linearly by 1% of FLC per 100 m up to a maximum of 2000 m)   |  |
|  | Ambient storage temperature - min                                     | -40 °C   |  |
|  | Ambient storage temperature - max                                     | 100 °C   |  |
| <b>Climatic environmental conditions</b> | Climatic proofing   | 95% relative humidity non-condensing at 40°C   |  |
|  | Operating temperature - min   |  |  |
|  | Operating temperature - max   | 80 °C  |  |
|  | Air discharge   | 8 kV (according to IEC/EN 61000-4-2)<br>Main: 2 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-4) Control: 1 kV, 5 kHz PC 1 (according to IEC/EN 61000-4-4)   |  |
|  | Burst Impulse   | 4 kV (according to IEC/EN 61000-4-2)   |  |
|  | Contact discharge   | 10 V/m, 80 - 1000 MHz and 1.4 - 2.0 GHz, PC 1  |  |
|  | Electromagnetic fields  | 3 V/m, 2.0 - 2.7 GHz, PC 1<br>10 V/m, 0.15 - 80 MHz, PC 1 (according to IEC/EN 61000-4-6)  |  |
|  | Immunity to line-conducted interference                               | Class A  |  |
|  | Radio interference class  | Main: 1 x 1-4 mm <sup>2</sup> , 2 x 1-4 mm <sup>2</sup> Control: 1 x 0.5-2.5 mm <sup>2</sup> , 2 x 0.5-2.5 mm <sup>2</sup><br>Main: 1 x 2.5-6 mm <sup>2</sup> , 2 x 2.5-6 mm <sup>2</sup> Control: 1 x 0.5-2.5 mm <sup>2</sup> , 2 x 0.5-2.5 mm <sup>2</sup><br>Main: 1 x 14-10, 2 x 14-10 Control: 1 x 18-12, 2 x 18-12 |  |
|  | Terminal capacity (flexible with ferrule)                             |  |  |
| <b>Terminal capacities</b>               | Terminal capacity (solid)   |  |  |
|  | Terminal capacity (solid/stranded AWG)                                |  |  |
|  | Terminal capacity (stranded)  |  |  |
|  | Tightening torque   | Main: 2.4 Nm (21.2 lb-in) Control: 0.5 Nm (4.4 lb-in)  |  |
|  | Screwdriver size  | Main: Pozidriv 2 Control: Pozidriv 1   |  |

|                             |  |  |
|-----------------------------|--|--|
| <b>Electrical rating</b>    | Operating voltage - max.   | 660 V  |
|                             | Operating voltage - min.   | 42 V   |
|                             | Rated operational current (Ie) at AC-1   | 12:00 am   |
|                             | Rated operational current (Ie) at AC-3   |  |
|                             | Rated operational current (Ie) at AC-51  | 100 A  |
|                             | Rated operational current (Ie) at AC-53A   | 20 A   |
|                             | Rated operational current (Ie) at AC-53B   |  |
|                             | Rated operational voltage (Ue) at AC - min                                       |  |
|                             | Rated operational voltage (Ue) at AC - max                                       |  |
|                             | Rated conditional short-circuit current, type 1, 600 Y/347 V                     | 65 kA  |
| <b>Short-circuit rating</b> | Rated conditional short-circuit current (Iq), type 2, 230 V                      | 10 kA  |
|                             | Rated conditional short-circuit current (Iq), type 2, 380 V, 400 V, 415 V        |  |
|                             |  |  |
| <b>Control circuit</b>      | Delay time   | 1/2 period   |
|                             | Drop-out time  | < 1/2 period   |
|                             | Drop-out voltage   | 1.2 V DC   |
|                             | Input current  | < 12 mA  |
|                             | Pick-up voltage  | 3.5 V DC   |
|                             | Rated control supply voltage (Us) at AC, 50 Hz - min                             | 0 V  |
|                             | Rated control supply voltage (Us) at AC, 50 Hz - max                             |  |
|                             | Rated control supply voltage (Us) at AC, 60 Hz - min                             |  |
|                             | Rated control supply voltage (Us) at AC, 60 Hz - max                             |  |
|                             | Rated control supply voltage (Us) at DC - min                                    | 4 V  |
| <b>Motor rating</b>         | Rated control supply voltage (Us) at DC - max                                    | 32 V   |
|                             | Horsepower   | 7.5 HP (230 V), 20 HP (480 V), 25 HP (600 V)                       |
|                             | Equipment heat dissipation, current-dependent                                    |  |
| <b>Design verification</b>  | Pvid   | 115 W  |
|                             | Heat dissipation per pole, current-dependent                                     |  |
|                             | Pvid   |  |
|                             | Rated operational current for specified heat dissipation (In)                    |  |
|                             | Static heat dissipation, non-current-dependent                                   |  |
|                             | Pvs  | 0 W  |
|                             | 10.2.2 Corrosion resistance  | Meets the product standard's requirements.                         |
|                             | 10.2.3.1 Verification of thermal stability of enclosures                         |  |
|                             | 10.2.3.2 Verification of resistance of insulating materials to normal heat       |  |
|                             | 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects |  |
|                             | 10.2.4 Resistance to ultra-violet (UV) radiation                                 | Please enquire   |
|                             | 10.2.5 Lifting   | Does not apply, since the entire switchgear needs to be evaluated. |
|                             | 10.2.6 Mechanical impact   |  |
|                             | 10.2.7 Inscriptions  |  |
|                             | 10.3 Degree of protection of assemblies  |  |
|                             | 10.4 Clearances and creepage distances   |  |
|                             | 10.5 Protection against electric shock   |  |

10.6 Incorporation of switching devices and components

10.7 Internal electrical circuits and connections Is the panel builder's responsibility.

10.8 Connections for external conductors

10.9.2 Power-frequency electric strength

10.9.3 Impulse withstand voltage

10.9.4 Testing of enclosures made of insulating material

10.10 Temperature rise

10.11 Short-circuit rating

10.12 Electromagnetic compatibility

10.13 Mechanical function

[IL034111ZU2021\\_09.pdf](#)

Wed Feb 23 2022

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

**Installation instructions**

**Date**