



TSXCTZ2A (45 004 56)

Opp/ned teller 40 kHz, 2 kanal



[Last ned produktdatablad for TSXCTZ2A](#)

[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

 Skjul

Produktspekter	Modicon TSX Micro automation platform
Produkt eller komponent type	Tellemodul
Counting input number	2
Counting frequency	40 Hz
Nettverksfrekvens	100 Hz
Forsyningsspenning	24 V DC 5 V DC
Input current	18 mA
Input voltage limits	5.5 V 5 V DC 19 - 30 V 24 V DC >= 2.4 V ved possisjon 1 5 V DC <= 1.2 V ved possisjon 0 5 V DC >= 11 V ved possisjon 1 24 V DC <= 5 V ved possisjon 0 24 V DC
Nåværende tilstand 0 garantert	<= 1 mA 5 V DC <= 2 mA 24 V DC
Nåværende tilstand 1 garantert	>= 6 mA 24 V DC >= 3.7 mA 5 V DC

Komplementær

 Skjul

Responstid	1.5 ms event processing 8 ms master task
Sensor power supply	< 2.5 V
Strømforbruk	15 mA
Logisk inngang	Positiv
Input impedance	1.4 Ohm 24 V DC at Un 0.27 Ohm 5 V DC at Un >= 0.44 Ohm 5 V DC at U = 2.4 V
Response tid	3 ms
Input type	Resistive 24 V DC
Input compatibility	2-wire/3-wire proximity sensor 24 V DC
Vekt	0.21 kg

Miljø

 Skjul

Standarder	IEC 1131 Type 2 24 V DC
------------	-------------------------

Bærekraftig

 Skjul

Bærekraftig	Ikke et Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0849 - Schneider Electric declaration of conformity