



Wood burning heater Harvia Pro 20 ES black

WKP200ES

The Harvia 20 RS Pro stove is a popular choice for cottage saunas thanks to its practicality. The right side of the stove features a fixed and easy-to-use 20-litre water tank that heats up the water while the stove is being heated for bathing.



Features

Net weight (kg) : 70.0

H x W x D : 760.0 x 430.0 x 650.0 mm

Stone amount (kg) : 40.0

ID	GTIN	Power	Sauna room size min - max m3
WKP200ES	6410082666867	24.1 kW	8.0-20.0

Related products



WL100

Spare parts

Product	ID	Pcs
Furnace grate	ZKIP-10	1
Connection pipe	ZKIP-130	1
Ashpan Pro 2019	Z2ES-127	1
Hinge pin	ZKIP-50	1
	Z2ES-1	1
	Z2ES-221	1
	ZES-146	1
Glass for stove door 184*210 mm	ZTS-36	1


Technical details

Technical data	Type / attribute	WKP200ES
	Color	Black
	Power output	24.1 kW
	Stone sizes	10-15 cm
	Stone amount (kg)	40
Dimensions	Product width (mm)	430
	Product height (mm)	760
	Product depth (mm)	650
	Net weight (kg)	70
	Gross weight	70.4
	Package width	515
	Package height	800
	Package depth	745
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	300
	Safety distance front (combustible materials)	300
	Safety distance right side (combustible materials)	300
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	300
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	300
	Safety distance (Ceiling) (depends on connections and therefore from output, star/delta)	1300
	Room min. height (depends on connections and therefore from output, star/delta)	2060

Technical images

1.1. Stove Parts


- A. Upper connection opening
- B. Rear connection opening
- C. Soot opening
- D. Stove door
- E. Ash box



Stove parts. Note! Only use replacement parts recommended by the manufacturer. Unauthorised modification of the stove is prohibited.


3.4. Accessories

- 3.4. Accessories**
- A. Harvía protective sheath WL1500.** Installed on the top of the upper connection opening. When a protective sheath or other protection is used that is not large enough to protect the inflammable materials around the stove from the heat radiation of the fire between the water heating and smoke pipe, you must install a radiation cover around the pipe.
- C. Radiation cover WZ0201130.** Installed around the smoke pipe.
- D. Harvía protective sheath WX017.**
- E. Harvía protective sheath WL400-WL775.**
- F. Harvía protective bedding WX018, WL100.** (not for models 20 RS/LS Pro, 36, 36 Duo, Premium VS, Linear 22 RS/LS, 22 RS/LS Pro).
- G. Harvía protective bedding WL110** (not for models ES Pro/S, ES Pro/S, 22 ES, 22 ES S).
- H. Angle smoke pipe. Different models.**
- I. Lead through flange for smoke pipe WZ020115.** Covers the edges of the flue opening and the sealing in the wall. Made of stainless steel. Consists of two parts to make it useable with differently inclined smoke pipes.
- J. Harvía WZ0201115.** Connected to the flue opening, does not require other seals. The inner side already has a seal.




Accessories (all dimensions in millimeters)

	A min.	B min.	C min.	D min.
M1, M2, M3 SL, Classic 140	1200	250	300	300
20 Pro, 20 SL Duo, 20 ES Pro, 20 SL Boiler, Premium V/S, Classic 220 Duo, 20 RS LS Pro	1300	300	300	300
26 Pro, Classic 280	1280	375	375	375
36, 36 Duo	1250	500	500	500
Linear 16, 16	1300	300	350	400
Linear 22, 22 S, Linear 22 RS LS ES, 22 RS LS ES	1265	400	380	500
Linear 28	1380	400	400	500




Safety distances (all dimensions in millimeters).

WX017	B min
M1, M2, M3/SL, 20 Pro, 20 SL Duo, 20 ES Pro/S, 20 Boiler, 20 SL Boiler, Premium, Classic 140 SL, Classic 220 Duo	300
26 Pro, Classic 280	375
Linear 16, 16	300
Linear 22/28, Linear 22 ES, 22 ES S, 22 S	400



		B min	C min	D min	F	
WL400/WL450	M1, M2, M3-SL 20 Pro SL Duo	50	50	300	30	
WL500/WL550	20 Boiler 30 SL Boiler	62	62	422	30	
WL600/WL650	20 ES Pro-S					
WL700/WL750	26 Pro	73	73	526	30	
WL800/WL850	30, 38 Duo	80	80	700	30	
WL900/WL950	20 ES Pro-S 22 RS SL Duo	82	82	422	30	
WL425/WL475	Linear 16, 16	30	30	400	32	
WL525/WL575	Linear 22, 22					
WL525/WL585	Linear 22, RS SL 22 RS SL S	70	70	500	40	
WL525/WL595	Linear 22 ES, 22 ES SL					
WL326/WL336						



Safety distances with protective sheaths (all dimensions in millimeters)