

PVCB100-PVC-BK : PVCB100

Art.-No. 172-02177 | PVCB100-PVC-BK | [Details](#)



This product is not available anymore.
Please contact our sales team. >




Base Data

| | |
|--------------------|--|
| Application | These commercial grade PVC sleeves (PVCB) have a heavier wall that makes them ideal for insulating wire in areas where greater protection is required. They can be supplied as continous tubing or cut lengths. The tubing is available in black only. |
| Colour | Black (BK) |
| Material | Polyvinylchloride - rigid molding grade (PVC) |
| Pack Cont. | 50 m |
| Package Content in | bag |
| PART DESCRIPTION | PVCB100-PVC-BK |

Product Dimensions

| | |
|-------------------|---------|
| Supplied Ø D min. | 10.0 mm |
| Wall (WT) | 0.65 mm |

Specifications

| | |
|---------------------------------|---|
| Dielectric Strength | 40 kV/mm |
| Dielectric Strength test method | IEC 60684 P2 |
| Flammability | UL 94 HB |
| Operating Temperature - °C | -65 °C to +105 °C, intermittent +135 °C |
| Specifications |  |
| Specifications | BS-2848 Type 3 |

Logistics and Packaging

| | |
|-------------------|---------------|
| Country of Origin | GB |
| Customs Number | 3917320090 |
| GTIN-13 / EAN | 5022660178948 |

More Information

| | |
|--------------|----------|
| ETIM 7.0 Key | EC002254 |
|--------------|----------|