

PVC Sleeving

Art.-No. 172-00161 | PVCB60BK-PVC-BK | **Details**



- Commercial grade PVC sleeving
- good for insulation and identification applications



More products in this product group:
Insulation Tubing >

Base Data

Application	A commercial grade of PVC sleeving with a high temperature rating.
Colour	Black (BK)
Description	PVC Sleeving
Material	Polyvinylchloride (PVC)
Pack Cont.	100 m
Package Content in	bag
PART DESCRIPTION	PVCB60BK-PVC-BK
Product Family	PVC Sleeving
Product Group	Insulation Tubing
Short Description	PVC 6mm Black (100m)

Product Dimensions

Inside Ø (ID)	6 mm
Supplied Ø D min.	5.0 mm
Wall (WT)	0.40 mm

Specifications

Dielectric Strength	40 kV/mm
Dielectric Strength test method	IEC 60684 P2
Flammability	UL 94 HB
Halogenfree	No
Operating Temperature - °C	-30 °C to +105 °C, intermittent +135 °C
Shelf Life	5 years
Specifications	
Specifications	BS-2848 Type 3
Tensile Strength	19 MPa
Test Method Tensile Strength	IEC 60684 P2

Logistics and Packaging

Country of Origin	GB
Customs Number	3917320090
GTIN-13 / EAN	5022660176630
Packaging 1 - Height (m)	0.33 m
Packaging 1 - Length (m)	0.09 m
Packaging 1 - Volume (m³)	0.0098 m³
Packaging 1 - Weight (kg)	3.75 kg
Packaging 1 - Width (m)	0.33 m
Storage Temperature	0 °C to +40 °C

More Information

ETIM 7.0 Key	EC002254
--------------	----------