

## PVC Sleeving

Art.-No. 172-00162 | PVCB80BK-PVC-BK | **Details**



- Commercial grade PVC sleeving
- good for insulation and identification applications



More products in this product group:  
Insulation Tubing >

### Base Data

|                    |                                                                    |
|--------------------|--------------------------------------------------------------------|
| Application        | A commercial grade of PVC sleeving with a high temperature rating. |
| Colour             | Black (BK)                                                         |
| Description        | PVC Sleeving                                                       |
| Material           | Polyvinylchloride (PVC)                                            |
| Pack Cont.         | 50 m                                                               |
| Package Content in | bag                                                                |
| PART DESCRIPTION   | PVCB80BK-PVC-BK                                                    |
| Product Family     | PVC Sleeving                                                       |
| Product Group      | Insulation Tubing                                                  |
| Short Description  | PVC 8mm Black (50m)                                                |

### Product Dimensions

|                   |         |
|-------------------|---------|
| Inside Ø (ID)     | 8 mm    |
| Supplied Ø D min. | 5.0 mm  |
| Wall (WT)         | 0.50 mm |

### Specifications

|                                 |                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------|
| Dielectric Strength             | 40 kV/mm                                                                            |
| Dielectric Strength test method | IEC 60684 P2                                                                        |
| Flammability                    | UL 94 HB                                                                            |
| Halogenfree                     | No                                                                                  |
| Operating Temperature - °C      | -30 °C to +105 °C, intermittent +135 °C                                             |
| Shelf Life                      | 5 years                                                                             |
| Specifications                  |  |
| Specifications                  | BS-2848 Type 3                                                                      |
| Tensile Strength                | 19 MPa                                                                              |
| Test Method Tensile Strength    | IEC 60684 P2                                                                        |

### Logistics and Packaging

|                           |                |
|---------------------------|----------------|
| Country of Origin         | GB             |
| Customs Number            | 3917320090     |
| GTIN-13 / EAN             | 5022660176647  |
| Packaging 1 - Height (m)  | 0.33 m         |
| Packaging 1 - Length (m)  | 0.09 m         |
| Packaging 1 - Volume (m³) | 0.0098 m³      |
| Packaging 1 - Weight (kg) | 4.80 kg        |
| Packaging 1 - Width (m)   | 0.33 m         |
| Storage Temperature       | 0 °C to +40 °C |

### More Information

|              |          |
|--------------|----------|
| ETIM 7.0 Key | EC002254 |
|--------------|----------|