Commercial grade PVC sleeving

Art.-No. 172-02130 | PVC50BK-PVC-BK | Details



- Commercial grade of PVC sleeving.
- Used as electrical insulation, physical protection and for decorative applications.

RoHS

More products in this product group: Insulating tubes >

Base Data

| Application | It can be used as electrical insulation, physical protection and for decorative applications. | |
|--------------------|---|--|
| Colour | Black (BK) | |
| Material | Polyvinylchloride (PVC) | |
| Pack Cont. | 100 m | |
| Package Content in | bag | |
| PART DESCRIPTION | PVC50BK-PVC-BK | |
| Product Family | Commercial grade PVC sleeving | |
| Product Group | Insulating tubes | |

Product Dimensions

| Diameter (D) | 5 mm |
|---------------|--------|
| Inside Ø (ID) | 5 mm |
| Wall (WT) | 0.4 mm |

Specifications

| Elongation at break | 270% |
|------------------------------|--|
| Flammability | self-extinguishing |
| Halogenfree | No |
| Operating Temperature - °C | -30 °C to +85 °C, intermittent +105 °C |
| Shelf Life | 5 years |
| Specifications | RoHS |
| Tensile Strength | 19 MPa |
| Test Method Tensile Strength | IEC 60684 P2 |

Logistics and Packaging

| Country of Origin | GB |
|---------------------|----------------|
| Customs Number | 39173200 |
| GTIN-13 / EAN | 5022660176272 |
| Storage Temperature | 0 °C to +40 °C |

More Information

|--|--|