

Commercial grade PVC sleeving

Art.-No. 172-02139 | PVC80TT-PVC-CL | Details



- Commercial grade of PVC sleeving.
- Used as electrical insulation, physical protection and for decorative applications.



More products in this product group: Insulating tubes >

Base Data

Application	It can be used as electrical insulation, physical protection and for decorative applications.		
Colour	Translucent (TT)		
Material	Polyvinylchloride (PVC)		
Pack Cont.	50 m		
Package Content in	bag		
PART DESCRIPTION	PVC80TT-PVC-CL		
Product Family	Commercial grade PVC sleeving		
Product Group	Insulating tubes		

Product Dimensions

Diameter (D)	8 mm	
Inside Ø (ID)	8 mm	
Wall (WT)	0.65 mm	

Specifications

Elongation at break	270%			
Flammability	self-extinguishing			
Halogenfree	No			
Operating Temperature - °C	-30 °C to +85 °C, intermittent +105 °C			
Shelf Life	5 years			
Specifications	RoHS			
Tensile Strength	19 MPa			
Test Method Tensile Strength IEC 60684 P2				

Logistics and Packaging

Country of Origin	GB
Customs Number	39173200
GTIN-13 / EAN	5022660176364
Storage Temperature	0 °C to +40 °C

More Information

ETIM 7.0 Key	EC002254		