

Commercial grade PVC sleeving

Art.-No. 172-02140 | PVC100WE-PVC-WH | Details



- Commercial grade of PVC sleeving.
- Used as electrical insulation, physical protection and for decorative applications.



More products in this product group:
[Insulating tubes >](#)

Base Data

Application	It can be used as electrical insulation, physical protection and for decorative applications.
Colour	White (WH)
Material	Polyvinylchloride (PVC)
Pack Cont.	50 m
Package Content in	bag
PART DESCRIPTION	PVC100WE-PVC-WH
Product Family	Commercial grade PVC sleeving
Product Group	Insulating tubes

Product Dimensions

Diameter (D)	10 mm
Inside Ø (ID)	10 mm
Wall (WT)	0.65 mm

Specifications

Elongation at break	270%
Flammability	self-extinguishing
Halogenfree	No
Operating Temperature - °C	-30 °C to +85 °C, intermittent +105 °C
Shelf Life	5 years
Specifications	
Tensile Strength	19 MPa
Test Method Tensile Strength	IEC 60684 P2

Logistics and Packaging

Country of Origin	GB
Customs Number	39173200
GTIN-13 / EAN	5022660176371
Storage Temperature	0 °C to +40 °C

More Information

ETIM 7.0 Key	EC002254
--------------	----------