

Commercial grade PVC sleeving
Art.-No. 172-02143 | PVC100TT-PVC-CL | Details



- Commercial grade of PVC sleeving.
- Used as electrical insulation, physical protection and for decorative applications.



More products in this product group:
[Insulating tubes >](#)

Base Data

| | |
|--------------------|---|
| Application | It can be used as electrical insulation, physical protection and for decorative applications. |
| Colour | Translucent (TT) |
| Material | Polyvinylchloride (PVC) |
| Pack Cont. | 50 m |
| Package Content in | bag |
| PART DESCRIPTION | PVC100TT-PVC-CL |
| Product Family | Commercial grade PVC sleeving |
| Product Group | Insulating tubes |

Product Dimensions

| | |
|---------------|---------|
| Diameter (D) | 10 mm |
| Inside Ø (ID) | 10 mm |
| Wall (WT) | 0.65 mm |

Specifications

| | |
|------------------------------|--|
| Elongation at break | 270% |
| Flammability | self-extinguishing |
| Halogenfree | No |
| Operating Temperature - °C | -30 °C to +85 °C, intermittent +105 °C |
| Shelf Life | 5 years |
| Specifications | |
| Tensile Strength | 19 MPa |
| Test Method Tensile Strength | IEC 60684 P2 |

Logistics and Packaging

| | |
|---------------------|----------------|
| Country of Origin | GB |
| Customs Number | 39173200 |
| GTIN-13 / EAN | 5022660176401 |
| Storage Temperature | 0 °C to +40 °C |

More Information

| | |
|--------------|----------|
| ETIM 7.0 Key | EC002254 |
|--------------|----------|