

# Commercial grade PVC sleeving

## Art.-No. 172-02158 | PVC50BU-PVC-BU | **Details**



- Commercial grade of PVC sleeving.
- Used as electrical insulation, physical protection and for decorative applications.

## RoHS

More products in this product group: Insulating tubes >

## **Base Data**

Application	It can be used as electrical insulation, physical protection and for decorative applications.	
Colour	Blue (BU)	
Material	Polyvinylchloride (PVC)	
Pack Cont.	100 m	
Package Content in	bag	
PART DESCRIPTION	PVC50BU-PVC-BU	
Product Family	Commercial grade PVC sleeving	
Product Group	Insulating tubes	

#### **Product Dimensions**

Diameter (D)	5 mm
Inside Ø (ID)	5 mm
Wall (WT)	0.4 mm

## **Specifications**

Elongation at break	270%
Flammability	self-extinguishing
Halogenfree	No
Operating Temperature - °C	-30 °C to +85 °C, intermittent +105 °C
Shelf Life	5 years
Specifications	RoHS V
Tensile Strength	19 MPa
Test Method Tensile Strength	IEC 60684 P2

## **Logistics and Packaging**

Country of Origin	GB
Customs Number	39173200
GTIN-13 / EAN	5022660176838
Packaging 1 - Height (m)	0.08 m
Packaging 1 - Length (m)	0.30 m
Packaging 1 - Type	reel
Packaging 1 - Volume (m³)	0.0072 m <sup>3</sup>
Packaging 1 - Weight (kg)	1 kg
Packaging 1 - Width (m)	0.30 m
Storage Temperature	0 °C to +40 °C

## **More Information**

ETIM 7.0 Key	EC002254	