

PRODUCT DATASHEET

LS P -1500/940/5/IP67

LED STRIP P 1500 P | High performance IP67 protected LED strips with 1500 lm/m for high requirements



Areas of application

- General indoor illumination
- General outdoor illumination
- Industry
- Offices, retail outlets and conference rooms
- Architecture lighting
- Decorative lighting

Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides
- Suitable for use in damp conditions thanks to high type of protection

Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 55.56 mm
- Lifetime (L70/B50): up to 50,000 h at Tc max.: 80°C
- Luminous flux: 1500 lm/m
- Very good color rendering index R_a : > 90
- Initial color consistency: < 3 SDCM
- Large range of color temperatures: from warm white to cool daylight
- Dimmable with suitable drivers, see also www.ledvance.com/dim
- Type of protection: IP67
- UV resistance (acc. IEC 60068-2-5)
- Salt mist resistance (acc. IEC 60068-2-52)

TECHNICAL DATA

Electrical data

Nominal wattage	60.00 W
Construction wattage	60.00 W
Nominal wattage per meter	12 W
Nominal voltage	24 V
Type of current	DC
Nominal current	27780 mA

Photometrical data

Luminous efficacy	121 lm/W
Luminous flux	6700 lm
Luminous flux per meter	1460 lm
Color temperature	4000 K
Color rendering index Ra	> 90
Light color LED	Daylight
Light color (designation)	Daylight
Standard deviation of color matching	<3 sdcn

Light technical data

Beam angle	110 °
Rated beam angle (half peak value)	110.00 °

LED MODULE INFORMATION

Number of LEDs per meter	144
Number of LEDs per module	720

Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	55.56 mm
Cable length	500.000 mm
Width	10.00 mm
Height	4.70 mm

Conductor cross section	0.5 mm ²
LED pitch	6.94 mm
Short pitch	Yes
Product weight	380.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+55 °C
Maximum temperature at tc test point	80 °C

Lifespan

Nominal lamp life time	50000 h
------------------------	---------

Capabilities

Dimmable	Yes ¹⁾
Lowest bending radius	30,0 mm
Self-adhesive	Yes

¹⁾ Dimmable with suitable drivers, see also www.ledvance.com/dim

Certificates & Standards

Approval marks – approval	CE / TUV / ENEC
Protection class	III
Type of protection	IP67
Energy class of contained Light source	E
Salt mist resistance acc. IEC 60068-2-52	Yes
UV resistance acc. IEC 60068-2-5	Yes

Energy labelling regulation data acc EU 2019/2015

EPREL ID	1032258
Model number	AC37963

EQUIPMENT / ACCESSORIES

- Connectors, profiles and covers for several mounting options available
- Endcaps have to be ordered separately

DOWNLOAD DATA

DOWNLOAD DATA	
	Addon Technical Information LS insert LED STRIP P IP67

DOWNLOAD DATA



Declarations of conformity
LS P



IES file (IES)
LS P-1500-940-5-IP67



LDT file (Eulumdat)
LS P-1500-940-5-IP67

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075706033	Folding box 1	242 mm x 242 mm x 26 mm	426.00 g	1.52 dm ³
4058075706040	Shipping box 20	550 mm x 325 mm x 270 mm	10453.00 g	48.26 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.