

# PRODUCT DATASHEET

## LS V -500/830/5

LED STRIP V 500 | LED strips with 500 lm/m for general applications



---

### Areas of application

- General indoor illumination
- Decorative illumination
- Private living areas

---

### Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides

---

### Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 30,000 h at Tc max.: 75°C
- Luminous flux: 500 lm/m
- Color rendering index R<sub>a</sub>: 80
- Large range of color temperatures: from warm white to cool daylight
- Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

## TECHNICAL DATA

### Electrical data

|                           |          |
|---------------------------|----------|
| Nominal wattage           | 24.00 W  |
| Construction wattage      | 24.00 W  |
| Nominal wattage per meter | 5 W      |
| Nominal voltage           | 24 V     |
| Type of current           | DC       |
| Nominal current           | 18750 mA |

### Photometrical data

|                                      |                        |
|--------------------------------------|------------------------|
| Luminous efficacy                    | 108 lm/W <sup>1)</sup> |
| Luminous flux                        | 2375 lm                |
| Luminous flux per meter              | 540 lm <sup>1)</sup>   |
| Color temperature                    | 3000 K                 |
| Color rendering index Ra             | > 80                   |
| Light color LED                      | Warm White             |
| Light color (designation)            | Warm White             |
| Standard deviation of color matching | ≤5 sdcm                |

<sup>1)</sup> Value based on first meter of the product

### Light technical data

|                                    |          |
|------------------------------------|----------|
| Beam angle                         | 120 °    |
| Rated beam angle (half peak value) | 120.00 ° |

### LED MODULE INFORMATION

|                           |     |
|---------------------------|-----|
| Number of LEDs per meter  | 70  |
| Number of LEDs per module | 350 |

### Dimensions & Weight



|                        |            |
|------------------------|------------|
| Length                 | 5000.00 mm |
| Length – smallest unit | 100 mm     |
| Cable length           | 500.000 mm |
| Width                  | 8.00 mm    |

|                         |                     |
|-------------------------|---------------------|
| Height                  | 1.50 mm             |
| Conductor cross section | 0.5 mm <sup>2</sup> |
| LED pitch               | 14.29 mm            |
| Short pitch             | No                  |
| Product weight          | 78.00 g             |

### Temperatures & operating conditions

|                                      |              |
|--------------------------------------|--------------|
| Ambient temperature range            | -20...+55 °C |
| Maximum temperature at tc test point | 75 °C        |

### Lifespan

|                        |         |
|------------------------|---------|
| Nominal lamp life time | 30000 h |
|------------------------|---------|

### Capabilities

|                       |                   |
|-----------------------|-------------------|
| Dimmable              | Yes <sup>1)</sup> |
| Lowest bending radius | 30,0 mm           |
| Self-adhesive         | Yes               |

<sup>1)</sup> Dimmable with suitable drivers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim)

### Certificates & Standards

|  |          |
|--|----------|
| Approval marks – approval                | CE / TUV |
| Protection class                         | III      |
| Type of protection                       | IP00     |
| Energy class of contained Light source   | F        |
| Salt mist resistance acc. IEC 60068-2-52 | No       |
| UV resistance acc. IEC 60068-2-5         | No       |


### Energy labelling regulation data acc EU 2019/2015

|              |         |
|--------------|---------|
| EPREL ID     | 1032265 |
| Model number | AC37970 |

### EQUIPMENT / ACCESSORIES

- Connectors, profiles and covers for several mounting options available
- Endcaps have to be ordered separately

### DOWNLOAD DATA

| DOWNLOAD DATA  |   |
|--|---|
|  | Addon Technical Information<br>LS Insert LED STRIP V IP00 |

## DOWNLOAD DATA



Declarations of conformity  
Declaration of Conformity LS V



IES file (IES)  
LS V-500-830-5



LDT file (Eulumdat)  
LS V-500-830-5

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075707818 | Folding box<br>1             | 242 mm x 242 mm x 26 mm              | 426.00 g     | 1.52 dm <sup>3</sup>  |
| 4058075707825 | Shipping box<br>30           | 450 mm x 420 mm x 230 mm             | 6403.00 g    | 43.47 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.