

Reference data

Eaton 5S 550i



Product	Eaton Ref	Short description
Eaton 5S 550i	5S550i	Professional UPS, compact protection for Workstations, 550VA/330W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 4 IEC outlets (3 with battery backup and surge protection + 1 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	330 x 164 x 328	5,53 kg	1 product / carton	743172436726
Complete pallet	1120 x 1200 x 1000	367 kg	63 cartons / pallet	

Package content
UPS + 2 IEC output power cords + USB Cable + 18-language User manual + Safety instructions

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	550 VA / 330 W
Size (H x W x D*)	250 x 87 x 260 mm
Weight	4,96 kg
Outlets	4 IEC outlets (3 with battery back up and surge protection + 1 with surge protection)
Output voltage	230 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional Warranty + contract for 3-year warranty (country specific)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report

Runtime in Minutes	10%	30%	50%	70%
5S 550i	65	18,5	9,5	5,5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 550VA/330W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 4 outlets : 3 with battery backup and lightning protection + 1 with lightning protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	66811

Reference data

Eaton 5S 700i



Product	Eaton Ref	Short description
Eaton 5S 700i	5S700i	Professional UPS, compact protection for Workstations, 700VA/420W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 6 IEC outlets (3 with battery backup and surge protection + 3 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	330 x 164 x 328	6,66 kg	1 product / carton	743172436894
Complete pallet	1120 x 1200 x 1000	442 kg	63 cartons / pallet	

Package content
UPS + 2 IEC output power cords + USB Cable + 18-language User manual + Safety instructions

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	700 VA / 420 W
Size (H x W x D*)	250 x 87 x 260 mm
Weight	5,98 kg
Outlets	6 IEC outlets (3 with battery back-up and surge protection + 3 with surge protection)
Output voltage	230 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional Warranty + contract for 3-year warranty (country specific)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report

Runtime in Minutes	10%	30%	50%	70%
5S 700i	62	18	8,5	5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 700VA/420W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 6 outlets : 3 with battery backup and lightning protection + 3 with lightning protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	66811

Reference data

Eaton 5S 1000i



Product	Eaton Ref	Short description
Eaton 5S 1000i	5S1000i	Professional UPS, compact protection for Workstations, 1000VA/600W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 8 IEC outlets (4 with battery backup and surge protection + 4 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	326 x 160 x 490	10,52 kg	1 product / carton	743172436962
Complete pallet	1113 x 1200 x 1000	461 kg	42 cartons / pallet	

Package content
UPS + 2 IEC output power cords + USB Cable + 18-language User manual + Safety instructions

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	1000 VA / 600 W
Size (H x W x D*)	250 x 87 x 382 mm
Weight	9,48 kg
Outlets	8 IEC outlets (4 with battery back-up and surge protection + 4 with surge protection)
Output voltage	230 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional Warranty + contract for 3-year warranty (country specific)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report

Runtime in Minutes	10%	30%	50%	70%
5S 1000i	93	27	14	8

Key selling points
<ul style="list-style-type: none"> • Ideal protection 1000VA/600W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 8 outlets : 4 with battery backup and lightning protection + 4 with lightning protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	66812

Reference data

Eaton 5S 1500i



Product	Eaton Ref	Short description
Eaton 5S 1500i	5S1500i	Professional UPS, compact protection for Workstations, 1500VA/900W, Line-Interactive with booster & fader, built-in surge protection, USB port, slim-line design, versatile form factor, Tel/Internet/Ethernet protection, 8 IEC outlets (4 with battery backup and surge protection + 4 with surge protection only)

Packaging	Size (H x W x D*mm)	Weight (kg)	Number of Units / Packaging	UPC Code
Individual packaging	326 x 160 x 490	12,12 kg	1 product / carton	743172437020
Complete pallet	1113 x 1200 x 1000	528 kg	42 cartons / pallet	

Package content
UPS + 2 IEC output power cords + USB Cable + 18-language User manual + Safety instructions

Technical specifications	
Technology	Line-Interactive (AVR with Booster + Fader)
Power output	1500 VA / 900 W
Size (H x W x D*)	250 x 87 x 382 mm
Weight	11,08 kg
Outlets	8 IEC outlets (4 with battery back-up and surge protection + 4 with surge protection)
Output voltage	230 V
Frequency	50 / 60 Hz auto-select
Input voltage range	175V-275V
Features	Automatic battery test, replaceable battery, resettable circuit breaker, audible alarm, permanent battery recharge (even when off), cold start
Data line protection	Tel/Internet/Ethernet protection
Power management	1 USB port, HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux)
Warranty	2 years ; optional Warranty + contract for 3-year warranty (country specific)
Technical standards	IEC 62040-1, IEC 62040-2, CE mark, CB Report

Runtime in Minutes	10%	30%	50%	70%
5S 1500i	97	25	11	7,5

Key selling points
<ul style="list-style-type: none"> • Ideal protection 1500VA/900W for Workstations • Automatic Voltage Regulation (AVR) • Compact slim-line design : saves desk space, versatile installation : vertical or horizontal • 8 outlets : 4 with battery backup and lightning protection + 4 with lightning protection only • 1 USB port (cable supplied), HID compliant for automatic integration into major OS (Windows, Mac OS X, Linux) • Tel/Fax/Modem/Internet/Ethernet protection • Replaceable battery • Audible alarm • Resettable circuit breaker

* H x W x D = Height x Width x Depth

Options	Reference
Warranty + (3 year-warranty)	66813