


Mer om VW3A5102

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VW3A5102**
Motordrossel 48A

EI-nummer: 4147491
EAN: 3389118065901

 [Last ned produktdatablad for VW3A5102](#)

Karakteristikk**Teknisk informasjon**

Produkt eller type komponent	Motor choke
Serie kompatibilitet	Altivar 71 Altivar 61
Produktspesifikk applikasjon	Output filter
[In] merkestrøm	48 A

Kompatibilitet	ATV61H075N4 ATV61HU15N4 ATV61HU22N4 ATV61HU30N4 ATV61HU40N4 ATV61W075N4 ATV61W075N4C ATV61WU15N4 ATV61WU15N4C ATV61WU22N4 ATV61WU22N4C ATV61WU30N4 ATV61WU30N4C ATV61WU40N4 ATV61WU40N4C ATV71H075N4 ATV71HU15N4 ATV71HU22N4 ATV71HU30N4 ATV71HU40N4 ATV71P075N4Z ATV71PU15N4Z ATV71PU22N4Z ATV71PU30N4Z ATV71PU40N4Z ATV71W075N4 ATV71WU15N4 ATV71WU22N4 ATV71WU30N4 ATV71WU40N4 ATV61HD11N4 ATV61HD11Y ATV61HD15N4 ATV61HD18N4 ATV61HU22S6X ATV61HU30M3 ATV61HU30S6X ATV61HU30Y ATV61HU40M3 ATV61HU40S6X ATV61HU40Y ATV61HU55M3 ATV61HU55N4 ATV61HU55S6X ATV61HU55Y ATV61HU75M3 ATV61HU75N4 ATV61HU75S6X ATV61HU75Y ATV61WD11N4 ATV61WD11N4C ATV61WD15N4 ATV61WD15N4C ATV61WD18N4 ATV61WD18N4C ATV61WU55N4 ATV61WU55N4C ATV61WU75N4 ATV61WU75N4C ATV71HD11N4 ATV71HD11Y ATV71HD15N4 ATV71HD18N4 ATV71HU15S6X ATV71HU22S6X ATV71HU22Y ATV71HU30M3 ATV71HU30S6X ATV71HU30Y ATV71HU40M3 ATV71HU40S6X ATV71HU40Y ATV71HU55M3 ATV71HU55N4 ATV71HU55S6X ATV71HU55Y ATV71HU75M3 ATV71HU75N4 ATV71HU75S6X ATV71HU75Y ATV71PD11N4Z ATV71PU55N4Z ATV71PU75N4Z ATV71WD11N4 ATV71WD15N4 ATV71WD18N4 ATV71WU55N4 ATV71WU75N4
Nedded quantity	1
Elektrisk tilkobling	Klemme, tilkoblingskapasitet: 10 mm2 / AWG 6
Komplementær	

Maximum motor cable length	200 m skjernet kabel 2,2...7,5 kW på 200 - 240 V 1 260 m uskjernet kabel 2,2...7,5 kW på 200 - 240 V 1 85 m skjernet kabel 0,75...18,5 kW på 380...480 V 1 95 m uskjernet kabel 0,75...18,5 kW på 380...480 V 1 50 m skjernet kabel 2,2...7,5 kW på 500...600 V 1 100 m uskjernet kabel 2,2...7,5 kW på 500...600 V 1 45 m skjernet kabel 2,2...11 kW på 500...690 V 1 70 m uskjernet kabel 2,2...11 kW på 500...690 V 1
DV/dt	500 V/µs maks på 400 V 750 V/µs maks på 500 V 1000 V/µs maks på 690 V
Varmetap	250 W
Tiltrekningsmoment	1,5 N.m
Maximum drive output frequency	100 Hz
Beskyttelsestype	Thermal protection av temperature-controlled switch, utløsertemperatur: 125 °C for <250 V AC, <0,5 A
Omgivelsestemperatur for drift	-10...50 °C
Vekt	8 kg
Miljø	
IP-grad	IP20 (med kits VW3A9612,613) IP00
Omgivelsestemperatur for lagring	-25...70 °C
Bærekraftig	
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Garantiperiode	
Garanti	18 months