

Mer om VW3A5104

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



VW3A5104

Motordrossel 215A X3

EI-nummer: 4147493
EAN: 3389118065727

Last ned produktdatablad for VW3A5104

Karakteristikk

Teknisk informasjon

Produkt eller type komponent	Motor choke
Serie kompatibilitet	Altivar 61Q Altivar 71Q Altivar 212 Altivar 71 Altivar Process ATV600 Altivar Process ATV900 Altivar 61
Produktspesifikk applikasjon	Output filter
[In] merkestrøm	215 A
Kompatibilitet	ATV61HD11N4 ATV61HD15N4 ATV61HD18N4 ATV61HU22S6X ATV61HU30S6X ATV61HU40S6X ATV61HU55N4 ATV61HU55S6X ATV61HU75N4 ATV61HU75S6X ATV61WD11N4 ATV61WD11N4C ATV61WD15N4 ATV61WD15N4C ATV61WD18N4 ATV61WD18N4C ATV61WU55N4 ATV61WU55N4C ATV61WU75N4 ATV61WU75N4C ATV71HD11N4 ATV71HD11Y ATV71HD15N4 ATV71HD18N4 ATV71HU15S6X ATV71HU22S6X ATV71HU30S6X ATV71HU40S6X ATV71HU55N4 ATV71HU55S6X ATV71HU75N4 ATV71HU75S6X ATV71PD11N4Z ATV71PU55N4Z ATV71PU75N4Z ATV71WD11N4 ATV71WD15N4 ATV71WD18N4 ATV71WU55N4 ATV71WU75N4 ATV212HU15N4 ATV61HD15Y ATV61HD18Y ATV61HD22N4 ATV61HD22Y ATV61HD30N4 ATV61HD30Y ATV61HD37N4 ATV61WD22N4 ATV61WD22N4C ATV61WD30N4 ATV61WD30N4C ATV61WD37N4 ATV61WD37N4C ATV71HD15Y ATV71HD18Y ATV71HD22N4 ATV71HD22Y ATV71HD30Y ATV71HD37N4 ATV71WD30N4 ATV71WD37N4 ATV630 variable speed drive - 2,2 kW, 500...690 V Tre-fase

ATV630 variable speed drive - 3 kW, 500...690 V
 Tre-fase
 ATV630 variable speed drive - 4 kW, 500...690 V
 Tre-fase
 ATV630 variable speed drive - 5,5 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 7,5 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 11 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 2,2 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 3 kW, 500...690 V
 Tre-fase
 ATV930 variable speed drive - 4 kW, 500...690 V
 Tre-fase
 ATV930 variable speed drive - 5,5 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 7,5 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 11 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive, 3 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 5 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 7,5 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 10 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 15 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 3 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 5 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 7,5 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 10 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 15 hp, 600 V Tre-
 fase
 ATV212HD15M3X
 ATV212WD15N4
 ATV212WD15N4C
 ATV61HC11Y
 ATV61HC13Y
 ATV61HC16Y
 ATV61HD30M3X
 ATV61HD37M3X
 ATV61HD37Y
 ATV61HD45M3X
 ATV61HD45N4
 ATV61HD45Y
 ATV61HD55N4
 ATV61HD55Y
 ATV61HD75N4
 ATV61HD75Y
 ATV61HD90N4
 ATV61HD90Y
 ATV61QC11N4
 ATV61QC13Y
 ATV61WD45N4
 ATV61WD45N4C
 ATV61WD55N4
 ATV61WD55N4C
 ATV61WD75N4
 ATV61WD75N4C
 ATV61WD90N4
 ATV61WD90N4C
 ATV71HC11Y
 ATV71HC13Y
 ATV71HD30M3X
 ATV71HD37M3X
 ATV71HD37Y
 ATV71HD45M3X
 ATV71HD45N4
 ATV71HD45Y
 ATV71HD55N4
 ATV71HD55Y
 ATV71HD75N4
 ATV71HD75Y
 ATV71HD90N4
 ATV71HD90Y
 ATV71QC11Y
 ATV71QB90N4
 ATV71WD45N4
 ATV71WD55N4
 ATV71WD75N4
 ATV630 variable speed drive - 15 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 18,5 kW,
 500...690 V Tre-fase
 ATV630 variable speed drive - 22 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 30 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 37 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 45 kW, 500...690

V Tre-fase
 ATV630 variable speed drive - 55 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 75 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive - 90 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 15 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 18,5 kW,
 500...690 V Tre-fase
 ATV930 variable speed drive - 22 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 30 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 37 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 45 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 55 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 75 kW, 500...690
 V Tre-fase
 ATV930 variable speed drive - 90 kW, 500...690
 V Tre-fase
 ATV630 variable speed drive, 20 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 25 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 30 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 40 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 50 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 60 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 75 hp, 600 V Tre-
 fase
 ATV630 variable speed drive, 100 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 20 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 25 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 30 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 40 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 50 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 60 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 75 hp, 600 V Tre-
 fase
 ATV930 variable speed drive, 100 hp, 600 V Tre-
 fase

Nedded quantity	3
Elektrisk tilkobling	Tag connector M10

Komplementær

Maximum motor cable length	150 m skjernet kabel 30...45 kW på 200 - 240 V 1 300 m uskjernet kabel 30...45 kW på 200 - 240 V 1 200 m skjernet kabel 5,5...18,5 kW på 380...480 V 1 300 m uskjernet kabel 5,5...18,5 kW på 380...480 V 1 150 m skjernet kabel 22...30 kW på 380...480 V 1 300 m uskjernet kabel 22...30 kW på 380...480 V 1 150 m skjernet kabel 45...75 kW på 380...480 V 1 300 m uskjernet kabel 45...75 kW på 380...480 V 1 150 m skjernet kabel 2,2...7,5 kW på 500...600 V 1 250 m uskjernet kabel 2,2...7,5 kW på 500...600 V 1 250 m skjernet kabel 2,2...7,5 kW på 500...600 V 2 400 m uskjernet kabel 2,2...7,5 kW på 500...600 V 2 100 m skjernet kabel 2,2...30 kW på 500...690 V 2 150 m uskjernet kabel 2,2...30 kW på 500...690 V 1 150 m skjernet kabel 11...30 kW på 500...690 V 2 250 m uskjernet kabel 11...30 kW på 500...690 V 2 150 m skjernet kabel 30...160 kW på 500...690 V 1 250 m uskjernet kabel 30...160 kW på 500...690 V 1 250 m skjernet kabel 30...160 kW på 500...690 V 2 300 m uskjernet kabel 30...90 kW på 500...690 V 2 400 m uskjernet kabel 90...160 kW på 500...690 V 2 200 m skjernet kabel 37 kW på 380...480 V 1 300 m uskjernet kabel 37 kW på 380...480 V 1 200 m skjernet kabel 90 kW på 380...480 V 1 300 m uskjernet kabel 90 kW på 380...480 V 1
DV/dt	500 V/µs maks på 400 V 750 V/µs maks på 500 V 1000 V/µs maks på 690 V
Varmetap	430 W
Maximum drive output frequency	100 Hz
Omgivelsestemperatur for drift	-10...50 °C
Vekt	15,5 kg
Miljø	
IP-grad	IP20 (med kits VW3A9612,613) IP00
Omgivelsestemperatur for lagring	-25...70 °C
Bærekraftig	
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Garantiperiode	
Garanti	18 months