

COMFORT TWIST QUICK ISO

Dimmable multifunctional all-round downlight for 230V with Comfort Lens. Twist function makes it possible to twist the luminaire $2x150^{\circ}$ and tilt 30° – perfect if you want to direct the light or fit in a sloping ceiling for example. Selectable colour temperature via DIP–Switch ColourTemp directly in the luminaire. IP44 luminaire for use indoors and outdoors. Can be installed directly against insulation in 28mm secondary spaced boarding with 13mm plaster. Complete with dimmable driver, 3–pole push–in terminal for through wiring and strain relief for cable or flex hose 16 mm. Dimmable with most common dimmers on the market.

IP44 - SUITS MOST ENVIRONMENTS, INDOORS AND OUTDOORS

- Twist function: twist 2x150° and tilt 30°
- Selectable colour temperature via DIP-switch ColourTemp L80 100 000h Ta 25°C
- Approved for installation directly against insulation
- Perfect for secondary spaced boarding 28mm with 13mm plaster
- · Adapted for both indoor and outdoor use









COMFORT TWIST QUICK ISO

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminai:
7392971144634	White	2700K/3000K/4000K	420lm/470lm/510lm	36°	6,5W
7392971144641	Black	2700K/3000K/4000K	420lm/470lm/510lm	36°	6,5W
7392971144658	Brushed steel	2700K/3000K/4000K	420lm/470lm/510lm	36°	6,5W





























COMFORT TWIST QUICK ISO 6-PACK

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminaire
7392971144665	White	2700K/3000K/4000K	420lm/470lm/510lm	36°	6,5W
7392971144672	Black	2700K/3000K/4000K	420lm/470lm/510lm	36°	6,5W









































