



BMXEIA0100 (45 020 50)

M340 AS-i V3 master modul



Last ned produktdatablad for BMXEIA0100



[Endre dine utvalgskriterier](#) [Produktliste](#)

[Karakteristikk](#) | [Dimensions Drawings](#) | [Connections and Schema](#) | [Dokumenter og nedlastning](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

Teknisk informasjon

 Skjul

Produktspekter	Modicon M340 automation platform
Produkt eller komponent type	Master module
AS-Interface profil	M4 (master profile) S7.3 (slave profile) S7.A.7 (slave profile) S7.A.A (slave profile) S7.A.8 (slave profile) S7.A.9 (slave profile) S6.0 (slave profile)
Adressering	Standard og utvidet

Komplementær

 Skjul

Cycle time	5 ms for 31 10 ms for 62
Elektrisk tilkobling	1 hannkontakt SUB-D 3 pins
Slave nummer	124 slave(s) for discrete inputs and outputs - Standard 124 slave(s) for analog inputs and outputs - Standard 496 slave(s) for discrete inputs and outputs - utvidet 124 slave(s) for analog inputs and outputs - utvidet
Kabellengde mellom enheter	100 m 200 m line extension 300 m 2 repeaters 500 m 2 repeaters and the master at the middle
Lokal varslings	1 LED for FAULT 1 LED grønn for module active (RUN) 1 LED rød for module error (ERR) 1 LED grønn for displays the group of 31 slaves (A/B) 1 LED rød for I/O module fault (I/O) 32 LEDs for diagnostics of the AS-Interface and each slave 1 LED grønn for external power supply present 1 LED rød for line fault 1 LED for ASI power
Strømforbruk	160 mA på 3.3 V DC
Modul format	Standard
Vekt	0.34 kg

Miljø

 Skjul

Produktsertifikater	AS-Interface No 86601
Omgivelsestemperatur drift	0...60 °C
Omgivelsestemperatur for lagring	-40...70 °C
IP-grad	IP20

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Tilgjengelig