

ROOFTOP PYRAMID ST FIXED STRUT SUPPORT, 10" X 4.8"

CATALOG NUMBER

PSF10C



CERTIFICATIONS



FEATURES

Provides superior support for pipe, conduit, duct, cable tray and equipment Foam bottom offers low abrasion interface for better roof membrane protection Compatible with roof surfaces including single ply, bituminous, metal and spray foam Provides superior load distribution, even with varying rooftop surfaces Ready to use out of the box, saving installation time and labor Multiple sizes and load ratings offer the ability to tailor the solution to the application Easy to transport to the roof Hot-dip galvanized and UV stabilized for long lasting performance

PRODUCT ATTRIBUTES

Article Number: 360464

Material: Polyethylene;Polypropylene;Steel


Finish: Hot-Dip Galvanized

Temperature: -45 to 65 °C
Static Load Safety Factor: 3:1
Length 2: 317.5 mm
Length 1: 254 mm
Height: 122 mm
Width: 203 mm
Surface Area: 59,355 mm²
Unit Weight: 1 kg
Static Load: 4,450 N

ADDITIONAL PRODUCT DETAILS

Static load at 73.1 kPa (10.6 psi) roof loading. Contact project or roofing engineer for maximum allowable load on individual project roof system.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Nord-Amerika

+1.800.753.9221 Option 1 – Customer Care Option 2 – Technical Support

Europa

Netherlands: +31 800-0200135 France: +33 800 901 793

Europa

Germany: 800 1890272 Other Countries: +31 13 5835404

APAC

Shanghai: + 86 21 2412 1618/19 Sydney: +61 2 9751 8500



Our powerful portfolio of brands:

Our powerful portfolio of brands: CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER nVent.com

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of

their respective owners. nVent reserves the right to change specifications without notice.