



CAVITY PLUG, W/SCREW, M5 SCREW, 1.811" SCREW

CATALOG NUMBER

MFV537



FEATURES

For use in plasterboard, hollow brick, hollow block and chipboard

Ideal for attachment to cavity walls

Large seating area for high loading capacity

PRODUCT ATTRIBUTES

Article Number: 571470

Screw Included: Yes

Material: Steel

Finish: Electrogalvanized

Screw Diameter: M5

Screw Length: 46 mm

Drill Bit Diameter: 10 mm

A: 5 – 14 mm

B: 12 mm


Ultimate Static Load 1: 200 N

Ultimate Static Load 2: 200 N

ADDITIONAL PRODUCT DETAILS

Refer to Ultimate Static Load 1 when anchor is set in plasterboard. Refer to Ultimate Static Load 2 when anchor is set in hollow block or hollow cinder block.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Nord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER