



FPN UNIVERSAL ANCHOR

CATALOG NUMBER

FPN6



FEATURES

- Expansion fixing for wood or drywall / plasterboard screws
- For use in concrete, brick and lightweight concrete

PRODUCT ATTRIBUTES

Article Number: 570710
Material: Nylon
Static Load Safety Factor: 5:1
Screw Diameter: 3.50 – 5.00 mm
Length: 30 mm
Drill Bit Diameter: 6 mm
Drill Hole Depth: 35 mm
Static Load 1: 600 N
Static Load 2: 450 N
Static Load 3: 450 N

ADDITIONAL PRODUCT DETAILS

Refer to Static Load 1 when anchoring in non-cracked concrete C20/25. Refer to Static Load 2 when anchoring in solid brick Mz 20. Refer to Static Load 3 when anchoring in solid sand-lime brick KS 20.

Static loads are calculated using the maximum Screw Diameter.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Nord-Amerika

+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa

Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa

Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC

Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER