

STRUT NUT WITH SPRING, CHANNEL TYPE A, STEEL, HOT-DIP GALVANIZED

CATALOG NUMBER

SPRAM10HD



FEATURES

Used to create metal frames with nVent CADDY Eristrut channels

Spring allows for easy installation

PRODUCT ATTRIBUTES

Article Number: 315100

Material: Steel

Finish: Hot-Dip Galvanized

Static Load Safety Factor: 3:1


Rod Size: M10

Thickness: 8 mm

Torque: 55 N-m

DIAGRAMS





| Pull-Out Strength | | | |
|-------------------|-------------------|--------|--------|
| Part Number | Channel Thickness | | |
| | 2,5 mm | 2 mm | 1,5 mm |
| SPRAM6xx | 2000 N | 2000 N | 2000 N |
| SPRAM8xx | 3330 N | 3330 N | 3330 N |
| SPRAM10xx | 4890 N | 4440 N | 4440 N |
| SPRAM12xx | 4890 N | 4660 N | 4440 N |
| SPRAM12Txx | 5670 N | 5050 N | 4440 N |

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Nord-Amerika

+1.800.753.9221

Option 1 - Customer Care

Option 2 - Technical Support

Europa

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europa

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500

