

- worldwide English



Fuse, fuse-link, low voltage, 2 A, AC 690 V, 14 x 51 mm, aM, IEC, cylindrical, motor protection, for industrial applications, IEC 60269-2

-



- [Delivery program](#)
- [Technical data ETIM 8.0](#)

Delivery program

Product range
Fuse
Basic function
Fuse-link
Field of application
low voltage
Rated current [I]
2 A
Rated voltage
AC 690 V
Size
14 x 51 mm
Utilization category
aM
Breaking Capacity
80 kA
usable for size/applications
motor protection
for industrial applications
Standard/Approval
IEC
Shape
cylindrical
Standards/Regulations
IEC 60269-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts /
Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])
Model
Ceramic fuse
Size
14x51 mm
Voltage type
AC
Rated current
2 A
Rated voltage
690 V
Utilization category
aM (switchgear protection)
Rated operating frequency
45 - 62 Hz
Type of fuse status indicator
Other
Release characteristic
Other
Breaking capacity
80 kA
Power loss at rated current
0.24 W

Product photo



c14m1_b

Photo



c14m1_c

Photo



c14m1_l

Photo



c14m1_r

Photo



c14m2_b

Photo



c14m2_c

Photo



c14m2_pkg

Photo



c14m2_r

Photo

Declaration of Conformity

EU

- [Low voltage cylindrical fuse-links \(DA-DC-00003494\)](#)
Asset
(PDF)

UK

- [Low voltage cylindrical fuse-links \(DA-DC-00004021\)](#)
Asset
(PDF)

Download-Center

- [Download-Center \(this item\)](#)
Eaton EMEA Download-Center - download data for this item
- [Download-Center](#)



[Generate data sheet in PDF format](#)



[Generate data sheet in Excel format](#)



[Write a comment](#)

[Imprint](#) [Privacy Policy](#) [Legal Disclaimer](#) [Terms and Conditions](#)

© 2022 by Eaton Industries GmbH

