



Fuse-link, low voltage, 0.5 A, AC 500 V, 120 kA, 10 x 38 mm, aM, IEC

Part no. **CYLINDRICAL FUSE 10x38 0.5A AM 500V AC**
 Catalog No. **C10M0.5**

EL-Nummer **1600256**
 (Norway)

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	0.5
Rated voltage			AC 500 V
Size			10 x 38 mm
Utilization category			aM
Breaking Capacity		kA	120
usable for size/applications			motor protection for industrial applications
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Miniature fuse (ecl@ss10.0.1-27-14-20-01 [AFZ796015])			
Model			Ceramic fuse
Size			10x38 mm
Voltage type			AC
Rated current		A	0.5
Rated voltage		V	500
Utilization category			aM (switchgear protection)
Rated operating frequency		Hz	45 - 62
Type of fuse status indicator			Other
Release characteristic			Other
Breaking capacity		kA	120
Power loss at rated current		W	0.49