


Tekniske data SICON mekaniske kabelsko og skjøtehylser


– også for fintråda leder uten bruk av ekstra hylse

Skjøtehylse, avgrening




El-nr.	Varenr. (Al + Cu)	RE  mm ²	RM  mm ²	SE  mm ²	SM  mm ²	RM kompr.  mm ²	Montasje- mål		Antall skruer	L1 mm	Ytre øD mm	Indre ød mm
20 935 40	332 447 010	50 – 240	50 – 185	50 – 185	50 – 150	50 – 240	–	SW 6	6	162	–	20

Skjøtehylse, skru



20 935 48	332 601 010	10 – 95	10 – 95	50 – 95	35 – 70	10 – 95	–	SW 5	2	65	24	13
20 935 53	332 607 010	25 – 150	25 – 150	35 – 120	35 – 120	25 – 150	–	SW 5	2	68	28	16,3
	332 593 010	25 – 150	25 – 150	35 – 120	35 – 120	25 – 150	–	SW 5	4	102	28	16,3
	332 592 010	50 – 240	50 – 185	50 – 185	50 – 150	50 – 240	–	SW 6	4	126	33	20
20 935 56	332 614 010	50 – 240	50 – 240	50 – 240	50 – 240	50 – 240	–	SW 6	4	126	35	21
20 935 62	332 602 010	95 – 400	95 – 300	95 – 240	95 – 240	95 – 300	–	SW 8	4	140	38	24
20 935 61	332 617 010	185 – 500	185 – 400	185 – 240	185 – 240	185 – 400	–	SW 8	6	170	42	26
20 935 39	332 603 010	300 – 800	300 – 630	–	300 – 400	300 – 630	–	SW 8	6	230	50	33,3

Kabelsko, skru



20 935 51	332 604 010	10 – 95	10 – 95	50 – 95	35 – 70	10 – 95	13	SW 5	1	70	24	13
20 935 46	332 599 010	25 – 150	25 – 150	35 – 120	35 – 120	25 – 150	13	SW 5	2	91	28	16,3
20 935 44	332 595 010	50 – 240	50 – 185	50 – 185	50 – 150	50 – 240	13	SW 6	2	115	33	20
	332 595 011	50 – 240	50 – 185	50 – 185	50 – 150	50 – 240	16,5	SW 6	2	115	33	20
20 935 52	332 605 010	95 – 400	95 – 300	95 – 240	95 – 240	95 – 300	13	SW 8	2	120	38	24
20 935 55	332 605 011	95 – 400	95 – 300	95 – 240	95 – 240	95 – 300	16,5	SW 8	2	120	38	24
20 935 58	332 625 010	185 – 500	185 – 400	185 – 240	185 – 240	185 – 400	13	SW 8	3	138	42	26
20 935 59	332 625 011	185 – 500	185 – 400	185 – 240	185 – 240	185 – 400	16,5	SW 8	3	138	42	26
20 935 60	332 606 010	300 – 800	300 – 630	–	300 – 400	300 – 630	16,5	SW 8	3	180	50	33,3

Kabelsko med sentrisk fane på forespørsel.

Verktøy:

Ved bruk av muttertrekker (anbefales) må oppgitt kraft / dreiemoment være 185 Nm eller mer.

(Eksempelvis Panasonic EY7541 eller Milwaukee C18 IW).



Holdeverktøy for mekaniske hylser og sko (dersom ikke muttertrekker benyttes)

El-nr.	Varenr.	Diameter mm	Tverrsnitt mm ²	Lengde mm
88 541 10	331 901 900	14 - 35	25 - 240	280
88 541 11	0797	25 - 50		300

MAXETA

Postboks 177 Sentrum, 3701 Skien
Tlf. 35 91 40 00 - faks 35 91 40 10
maxeta@maxeta.no - www.maxeta.no