



A9C70132 (16 063 05)

Aut.gjeninnk. ARA iC60 1-2P



[Last ned produktdatablad for A9C70132](#)



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Serie	Acti 9
Produkt eller komponent type	Automatic recloser auxiliary
Kortnavn utstyr	ARA iC60
Signalkontakt type	2 OF potensialfri kontakt
Signalling circuit voltage	24 V 10 mA AC/DC 230 V 1 A AC

Komplementær

[Skjul](#)

Start/stopp	Inhibition of automatism maintained 230 V AC 50/60 Hz Ultimate reclosing impuls 230 V AC 50/60 Hz
Input current	5 mA
Varighet på impuls	>= 200 ms styrekrets
Responstid	< 500 ms
[Us] merkespenning	230 V AC 50/60 Hz
Effektforbruk	2 W
[Ui] isolasjonsspenning	400 V
[Uimp] Nominell impulsspenning	6 kV
Verdien av innstillingen	Program 1 : 1 reclosing attemp, short cycle <= 10 s before reclosing / 6 min check time Program 2 : 3 reclosing attemps, short cycle <= 10 s before reclosing / 2 min check time Program 2 : 3 reclosing attemps, short cycle <= 1 min before reclosing / 6 min check time Program 2 : 3 reclosing attemps, short cycle <= 3 min before reclosing / 6 min check time Program 3 : 5 reclosing attemps, long fixed cycle <= 10 s before reclosing / 2 min check time Program 3 : 5 reclosing attemps, long fixed cycle <= 1 min before reclosing / 6 min check time Program 3 : 5 reclosing attemps, long fixed cycle <= 3 min before reclosing / 6 min check time Program 4 : 5 reclosing attemps, long progressive cycle <= 10 s before reclosing / 2 min check time Program 4 : 5 reclosing attemps, long progressive cycle <= 1 min before reclosing / 6 min check time Program 4 : 5 reclosing attemps, long progressive cycle <= 3 min before reclosing / 8 min check time Program 4 : 5 reclosing attemps, long progressive cycle <= 4 min before reclosing / 10 min check time Program 4 : 5 reclosing attemps, long progressive cycle <= 5 min before reclosing / 12 min check time
Lokal varslng	Blinker Orange LED: not operational Blinker grønn LED: normal drift Blinker rød LED: reclosing cycle in progress Fixed rød LED: automatic recloser locked
Monteringsmetode	Klips på
Montering	DIN skinne
Kam samleskinne fordelingsblokk kompatibilitet	Nei
9 mm polbredde	7
Høyde	93 mm
Bredde	63 mm
Dybde	75.5 mm
Vekt	440 g
Farge	Hvit

Elektrisk levetid	5000 sykluser
Tilpasset for hengelås	Låsbar med hengelås
Avmantlings lengde	Strømforsyning: 10 mm (Bunn) Inngang: 10 mm (Bunn) Utgang: 8 mm (Topp)
Tiltrekningsmoment	Strømforsyning: 1 N.m Inngang: 1 N.m Utgang: 0.7 N.m
Kompatibel med	Acti 9: Acti 9 iC60
Kompatibilitet	IC60 2P IC60 1P + N IC60 1P

Miljø

 Skjul

IP-grad	IP20 i henhold til IEC 60529
Forurensningsgrad	3 i samsvar med IEC 60947
Overspenningskategori	II
Tropisk beskyttelse	2
Relativ fuktighet	93 % på 40 °C
Omgivelsestemperatur for lagring	-40...70 °C
Omgivelsestemperatur drift	-25...60 °C

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 1312 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Tilgjengelig