



03006 (24 620 08)

Din skinne 750mm



Last ned produktdatablad for 03006



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon



Serie	Prisma
Kompatibel med	Prisma G
Produkt eller komponent type	Skinne
Tilbehør / separat del kategori	Installasjonstilbehør
Type festeskinne	Modulær
Installert utstyr	Multi 9: fast modular device Acti 9: fast modular device Multi 9: fast modular device <= 40 A Acti 9: fast modular device <= 40 A Multi 9: fast NG125 uten earth leakage protection - control: vippe Multi 9: fast NG125 med earth leakage protection Compact: fast INS40 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS63 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS100 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS125 - control: direct front rotary handle - Vertikal installasjon Compact: fast INS160 - control: direct front rotary handle - Vertikal installasjon Acti 9: fast iC120 med earth leakage protection - control: vippe Acti 9: fast iC120 uten earth leakage protection - control: vippe
Polene beskrivelse	12 x 2P: fast: NG125 6 x 2P: fast: NG125 8 x 3P: fast: NG125 4 x 3P: fast: NG125 6 x 4P: fast: NG125 3 x 4P: fast: NG125 24 x 1P: fast: iC120 4 x 3P: fast: INS40 Vertikal installasjon 4 x 3P: fast: INS63 Vertikal installasjon 4 x 3P: fast: INS100 Vertikal installasjon 4 x 3P: fast: INS125 Vertikal installasjon 4 x 3P: fast: INS160 Vertikal installasjon 6 x 4P: fast: iC120 3 x 4P: fast: iC120 4 x 4P: fast: INS40 Vertikal installasjon 4 x 4P: fast: INS63 Vertikal installasjon 4 x 4P: fast: INS100 Vertikal installasjon 4 x 4P: fast: INS125 Vertikal installasjon 4 x 4P: fast: INS160 Vertikal installasjon 12 x 2P: fast: iC120 8 x 3P: fast: iC120 5 x 2P: fast: iC120 3 x 3P: fast: iC120

Komplementær



Skap/kapsling beskrivelse	Floor-standing enclosure - width 850 mm
Antallet vertikale moduler (50 mm)	5 module(s) : iC120 without earth leakage protection , direct in 850 mm Wide floor-standing enclosure 4 module(s) : INS100 , direct in 850 mm Wide floor-standing enclosure 5 module(s) : INS100 , direct in 850 mm Wide floor-standing enclosure 4 module(s) : INS125 , direct in 850 mm Wide floor-standing enclosure 5 module(s) : INS125 , direct in 850 mm Wide floor-standing enclosure 4 module(s) : INS160 , direct in 850 mm Wide floor-standing enclosure 5 module(s) : INS160 , direct in 850 mm Wide floor-standing enclosure 4 module(s) : INS40 , direct in 850 mm Wide floor-standing enclosure 4 module(s) : INS63 , direct in 850 mm Wide floor-standing enclosure 3 module(s) : modular device <= 40 A , direct in 850 mm Wide floor-standing enclosure 4 module(s) : modular device , direct in 850 mm Wide floor-standing enclosure 5 module(s) : NG125 without earth leakage protection , direct in 850 mm Wide floor-standing enclosure 5 module(s) : iC120 with earth leakage protection , direct in 850 mm

	Wide floor-standing enclosure 5 module(s) : NG125 with earth leakage protection , direct in 850 mm Wide floor-standing enclosure
9 mm polbredde	72
Antall pr. sett	Sett á 1
Høyde	35 mm
Bredde	662 mm
Dybde	15 mm
Vekt	0.3 kg
Farge	Grå
Tykkelse	1.5 mm

Miljø

 Skjul

Standarder	IEC 61439-2 IEC 61439-1
-------------------	----------------------------

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 0807 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Krever ingen spesiell avfallshåndtering