

## PKPM3, 3-pole - Technical Data sheet

### Technical Data

		<b>PKPM3, 3-pole</b>
<b>Electrical</b>		
Design according to		IEC/EN 61009
Current test marks as printed onto the device		
Line voltage-independent tripping		instantaneous 250 A (8/20 $\mu$ s), surge current proof
Rated voltage	$U_e$	30 mA types: 230 V AC; 50 Hz 100 mA types: 230/400 V AC; 50 Hz
Rated tripping current	$I_{\Delta n}$	30, 100 mA
Rated non-tripping current	$I_{\Delta no}$	0.5 $I_{\Delta n}$
Sensitivity		AC and pulsating DC
Selectivity class		3
Rated breaking capacity	$I_{cn}$	10 kA
Rated current		10 - 20 A
Rated impulse withstand voltage	$U_{imp}$	4 kV (1.2/50 $\mu$ s)
Characteristic		B, C
Maximum back-up fuse (short-circuit)		100 A gL (>10 kA)
Endurance		
electrical components		$\geq 2,000$ switching operations
mechanical components		$\geq 10,000$ switching operations
<b>Mechanical</b>		
Frame size		45 mm
Device height		80 mm
Device width		70 mm (4 MU)
Mounting		3-position DIN rail clip, permits removal from existing busbar system
Degree of protection, switch		IP20
Degree of protection, built-in		IP40
Upper and lower terminals		open-mouthed/lift terminals
Terminal protection		finger and hand touch safe, DGUV VS3, EN 50274
Terminal capacity		1 - 25 mm <sup>2</sup>
Terminal torque		2 - 2.4 Nm
Busbar thickness		0.8 - 2 mm
Operating temperature		-25°C to +40°C
Storage- and transport temperature		-35°C to +60°C
Resistance to climatic conditions		according to IEC/EN 61009