

COMFORT G4 QUICK ISO

With its high lumen output and polished lens technology, we present our popular fixture with Comfort Lens as generation 4! High performance downlights made for a sustainable future – easily dismantled to save time when recycling. Fixed or adjustable, now with ISO cover for installation in 28mm secondary spaced boarding and approved for installation directly against insulation. Easily installed with very good colour rendering, $R_a > 95$, that is just as good indoors as outdoors. Tilttable version (30°) is the perfect choice of luminaire for sloping ceilings. Driver with cover that can be adapted for cable or flex hose 16mm. Comes with 3-pole push-in terminal for through wiring and strain relief.





**WITH ISO COVER FOR
INSTALLATION DIRECT
AGAINST INSULATION**

- Lifetime L80 100 000h Ta 25°C
- Newly developed dimmable driver with combined cover for cable or flex hose 16mm
- Replaceable LED and driver – built for the future
- Low-build, perfect for secondary spaced boarding 28mm with 13mm plaster
- Approved for installation directly against insulation
- Can be installed both indoors and outdoors





COMFORT G4 QUICK ISO

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminaire
7392971146478 ¹⁾	White	Tune 2000-2700K	520lm	36°	7,5W
7392971146485	White	2700K	650lm	36°	7,5W
7392971146492	White	3000K	690lm	36°	7,5W






COMFORT G4 QUICK ISO TILT

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminaire
7392971146508 ¹⁾	White	Tune 2000-2700K	520lm	36°	7,5W
7392971146515 ¹⁾	White	Tune 2000-2700K	520lm	60°	7,5W
7392971146522	White	2700K	650lm	36°	7,5W
7392971146539	White	2700K	650lm	60°	7,5W
7392971146546	White	3000K	690lm	36°	7,5W
7392971146553	White	3000K	690lm	60°	7,5W
7392971146560 ¹⁾	Brushed steel	Tune 2000-2700K	520lm	36°	7,5W
7392971146577	Brushed steel	2700K	650lm	36°	7,5W
7392971146584	Brushed steel	3000K	690lm	36°	7,5W



COMFORT G4 QUICK ISO TILT DALI

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminaire
7392971146621 ¹⁾	White	Tune 2000-2700K	520lm	36°	8W
7392971146638	White	2700K	650lm	36°	8W
7392971146645	White	3000K	690lm	36°	8W



COMFORT G4 QUICK ISO TILT 6-PACK

GTIN	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Power Luminaire
7392971146591 ¹⁾	White	Tune 2000-2700K	520lm	36°	7,5W
7392971146607	White	2700K	650lm	36°	7,5W
7392971146614	White	3000K	690lm	36°	7,5W

