



Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

Teknisk informasjon

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Merkeeffekt i W	700 W
Merkeeffekt VA	1000 VA
Input Connection Type	IEC 320 C14
Output connection type	4 IEC 320 C13 2 IEC Jumpers
Antall rack-enhet	2U
Antall kabler	1
Batteritype	Bly-syre batteri
Inkludert utstyr	Documentation CD Installation guide Rack mounting support rails USB kabel

Generelt

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Cloud-enabled monitoring
Overflødig	No

Fysisk

Farge	Sort
Høyde	8,6 cm
Bredde	43,2 cm
Dybde	47,7 cm
Vekt	22,5 kg
Montasjeplassering	Front
Mounting preference	Lower
Monteringsmetode	Rack-mounted

Two post mountable	0
USB kompatibel	Yes

Input

Toleranse forsyningsspenning	151...302 V Justrbar 160...286 V
Nettverksfrekvens	50/60 Hz +/- 3 Hz automatisk gjenkjenning

Output

Harmonisk forvrengning	Mindre enn 5 %
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	700 W
Overføringstid	6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Utgangsfrekvens	50/60 Hz +/- 3 Hz sync to mains

Overenstemmelse

Produktsertifikater	CSA EAC RCM VDE
Standarder	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Miljømessig

Akkustikknivå	45 dBA
Varmeavgivelse	56 Btu/t
Driftshøyde	0...10000 ft
Omgivelsestemperatur drift	0...40 °C
Omgivelsestemperatur for lagring	-15...45 °C
Storage altitude	0,00...15240,00 m
Relativ fuktighet	0...95 %
Storage Relative Humidity	0...95 %

Batteri og levetid

Tilleggsinformasjon	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Batteriopladingstid	3 t
Number of battery replacement quantity	1
Batterilevetid	4...6 år
Batterikraft i VAh	336 VAh runtime
Batteri ladekraft	112 W rated

Kommunikasjon og ledelse

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Kontrollpanel	Multifunction LCD status and control console
Nødstop	Optional
Ledige plasser	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Overspenningsbeskyttelse og filtrering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Forpakkingsinformasjon

Enhetstype pakke 1	PCE
Antall enheter i pakke 1	1
Pakke 1 Høyde	25,1 cm
Pakke 1 Bredde	59,4 cm
Pakke 1 Vekt	60,3 cm
Package 1 Weight	31,45 kg
Enhetstype pakke 2	P12
Antall enheter i pakke 2	4
Pakke 2 Høyde	75 cm
Pakke 2 Bredde	80 cm
Pakke 2 Lengde	120 cm
Pakke 2 Vekt	132 kg

Bærekraftig

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Garantiperiode

Garanti	3 years repair or replace (excluding battery) and 2 years for battery
---------	---