

SCL500RMI1UNC

APC Smart-UPS, Line Interactive, 500VA,
Lithium-ion, Rackmount 1U, 230V, 4x IEC C13
outlets, Network Card, Short Depth



Oversikt

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually in Stock

Teknisk informasjon

Main Input Voltage	230 V
Main Output Voltage	230 V
Merkeeffekt i W	400 W
Merkeeffekt VA	500 VA
Input Connection Type	IEC 60320 C14
Output connection type	4 IEC 60320 C13
Antall rack-enhet	1U
Batteritype	Li-Ion (Lithium-Ion)
Inkludert utstyr	Installation guide Rack mounting support rails USB kabel

Generelt

Number of power module filled slots	0
Number of power module free slots	0
Product web sub-family	Lithium-Ion
Overflødig	No

Fysisk

Farge	Black with silver front bezel
Høyde	4,4 cm
Bredde	43,2 cm
Dybde	23,2 cm
Vekt	4,1 kg
Montering	Gulv Vegg
Mounting preference	No preference
Monteringsmetode	Rack-mounted
Two post mountable	1
USB kompatibel	Yes

Input

Toleranse forsyningsspenning	208...253 V
Nettverksfrekvens	47...63 Hz

Output

Harmonisk forvrengning	Mindre enn 5 %
Maximum configurable power in VA	500 VA
Maximum configurable power in W	400 W
Overføringstid	6 ms typical : 10 ms maximum
Wave type	Sine wave
Utgangsfrekvens	50/60 Hz +/- 3 Hz sync to mains

Overenstemmelse

Produktsertifikater	C-Tick CE EAC
Merking	GS Mark
Standarder	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Miljømessig

Akkustikknivå	45 dBA
Driftshøyde	0...6561 ft
Omgivelsestemperatur drift	0...40 °C
Omgivelsestemperatur for lagring	-10...40 °C
Storage altitude	0,00...14999,82 m
Relativ fuktighet	10...90 % ikke-kondenserende
Storage Relative Humidity	10...90 % ikke-kondenserende

Batteri og levetid

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Batteriopladingstid	3 t
Batteriets design livslengde	5...10 år
Batterilevetid	8...10 år
Batterikraft i VAh	30 VAh runtime
Batteri ladekraft	10 W rated

Kommunikasjon og ledelse

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Kontrollpanel	LED Status display with on line : on battery
Ledige plasser	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Overspenningsbeskyttelse og filtrering

Surge energy rate	510 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Forpakkingsinformasjon

Enhetstype pakke 1	PCE
Antall enheter i pakke 1	1
Pakke 1 Høyde	16,8 cm
Pakke 1 Bredde	33,7 cm
Pakke 1 Vekt	59 cm
Package 1 Weight	6,49 kg

Bærekraftig

REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	Analyseres
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.

Garantiperiode

Garanti	5 year repair or replace
---------	--------------------------