





312 IP20 5W/830 PCO WH

Intermediate space luminaire

A sleek general-purpose LED luminaire for dry indoor spaces. Create indirect lighting by placing the LED Jatkos on top of a cabinet, for example. These lights can be connected in sequence up to 112 W either by attaching the luminaires directly to each other or with the provided 100 mm intermediate cord. Continuous lighting without dark spots. Beam width of 160°. Surface installation. Plug connection and a 1.8 m cord. On/off switch on the luminaire. Four different lengths available.

Led Jatkos Surface mounted luminaire 5W 3000K
550lm No dim; IP20; Protection cl. II; L70B50 30000h;
LED not exchangeable; CRI>80; SDCM6; Through-wired; Housing Plastic; Colour wh; Cover Plastic, opal



312 IP20 5W/830 PCO WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4146712 | A1KYKQ | 0.064 | Led Jatkos |

| Mounting | |
|--|---------------|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | Yes |
| Fit for monitor workplace | No |
| Degree of protection (IP) | IP20 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Through-wired |
| Number of poles | 2 |
| Connection type | Plug |

| Structure | |
|--|----------------------|
| Lamp type | LED not exchangeable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Plastic |
| Housing surface protection | Plastic-coated |
| Colour housing | White |
| Material cover | Plastic, opal |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | E |
| Emergency power supply integrated | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| Dimming depending on control gear | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|-------------------------------------|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Beam angle | Open beam |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Light outlet | Direct |
| Effective luminous flux (lm) | 550 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index CRI | 80-89 |
| Colour temperature switchable | No |
| Luminous flux adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|--|-------|
| Rated life time L70/B50 at 25 °C | 30000 |
| Rated ambient temperature acc. IEC62722-2-1 (min) [°C] | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) [°C] | 25 |

| Measurements | |
|-------------------|-----|
| Width (mm) | 23 |
| Height/depth (mm) | 37 |
| Length (mm) | 312 |

| Electrotechnical data | |
|-----------------------------------|---|
| Voltage type | AC |
| Nominal voltage (min) [V] | 220 |
| Nominal voltage (max) [V] | 240 |
| Type of control gear | LED operating device current-controlled |
| Protection class | II |
| Suitable for lamp power (min) [W] | 5 |
| Suitable for lamp power (max) [W] | 5 |
| Maximum system power [W] | 5 |
| Luminaire efficacy (lm/W) | 110 |





516 IP20 10W/830 PCO WH

Intermediate space luminaire

A sleek general-purpose LED luminaire for dry indoor spaces. Create indirect lighting by placing the LED Jatkos on top of a cabinet, for example. These lights can be connected in sequence up to 112 W either by attaching the luminaires directly to each other or with the provided 100 mm intermediate cord. Continuous lighting without dark spots. Beam width of 160°. Surface installation. Plug connection and a 1.8 m cord. On/off switch on the luminaire. Four different lengths available.

Led Jatkos Surface mounted luminaire 10W 3000K
1000lm No dim; IP20; Protection cl. II; L70B50 30000h;
LED not exchangeable; CRI>80; SDCM6; Through-wired; Housing Plastic; Colour wh; Cover Plastic, opal



516 IP20 10W/830 PCO WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4146713 | A1KYKT | 0.092 | Led Jatkos |

| Mounting | |
|--|---------------|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | Yes |
| Fit for monitor workplace | No |
| Degree of protection (IP) | IP20 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Through-wired |
| Number of poles | 2 |
| Connection type | Plug |

| Structure | |
|--|----------------------|
| Lamp type | LED not exchangeable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Plastic |
| Housing surface protection | Plastic-coated |
| Colour housing | White |
| Material cover | Plastic, opal |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | E |
| Emergency power supply integrated | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| Dimming depending on control gear | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|-------------------------------------|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Beam angle | Open beam |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Light outlet | Direct |
| Effective luminous flux (lm) | 1000 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index CRI | 80-89 |
| Colour temperature switchable | No |
| Luminous flux adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|--|-------|
| Rated life time L70/B50 at 25 °C | 30000 |
| Rated ambient temperature acc. IEC62722-2-1 (min) [°C] | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) [°C] | 25 |

| Measurements | |
|-------------------|-----|
| Width (mm) | 23 |
| Height/depth (mm) | 37 |
| Length (mm) | 516 |

| Electrotechnical data | |
|-----------------------------------|---|
| Voltage type | AC |
| Nominal voltage (min) [V] | 220 |
| Nominal voltage (max) [V] | 240 |
| Type of control gear | LED operating device current-controlled |
| Protection class | II |
| Suitable for lamp power (min) [W] | 10 |
| Suitable for lamp power (max) [W] | 10 |
| Maximum system power [W] | 10 |
| Luminaire efficacy (lm/W) | 100 |




849 IP20 13W/830 PCO WH

Intermediate space luminaire

A sleek general-purpose LED luminaire for dry indoor spaces. Create indirect lighting by placing the LED Jatkos on top of a cabinet, for example. These lights can be connected in sequence up to 112 W either by attaching the luminaires directly to each other or with the provided 100 mm intermediate cord. Continuous lighting without dark spots. Beam width of 160°. Surface installation. Plug connection and a 1.8 m cord. On/off switch on the luminaire. Four different lengths available.

Led Jatkos Surface mounted luminaire 13W 3000K
1400lm No dim; IP20; Protection cl. II; L70B50 30000h;
LED not exchangeable; CRI>80; SDCM6; Through-wired; Housing Plastic; Colour wh; Cover Plastic, opal



849 IP20 13W/830 PCO WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4146714 | A1KYKU | 0.138 | Led Jatkos |

| Mounting | |
|--|---------------|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | Yes |
| Fit for monitor workplace | No |
| Degree of protection (IP) | IP20 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Through-wired |
| Number of poles | 2 |
| Connection type | Plug |

| Structure | |
|--|----------------------|
| Lamp type | LED not exchangeable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Plastic |
| Housing surface protection | Plastic-coated |
| Colour housing | White |
| Material cover | Plastic, opal |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | E |
| Emergency power supply integrated | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| Dimming depending on control gear | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|-------------------------------------|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Beam angle | Open beam |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Light outlet | Direct |
| Effective luminous flux (lm) | 1400 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index CRI | 80-89 |
| Colour temperature switchable | No |
| Luminous flux adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|--|-------|
| Rated life time L70/B50 at 25 °C | 30000 |
| Rated ambient temperature acc. IEC62722-2-1 (min) [°C] | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) [°C] | 25 |

| Measurements | |
|-------------------|-----|
| Width (mm) | 23 |
| Height/depth (mm) | 37 |
| Length (mm) | 849 |

| Electrotechnical data | |
|-----------------------------------|---|
| Voltage type | AC |
| Nominal voltage (min) [V] | 220 |
| Nominal voltage (max) [V] | 240 |
| Type of control gear | LED operating device current-controlled |
| Protection class | II |
| Suitable for lamp power (min) [W] | 13 |
| Suitable for lamp power (max) [W] | 13 |
| Maximum system power [W] | 13 |
| Luminaire efficacy (lm/W) | 108 |





1149 IP20 18W/830 PCO WH

Intermediate space luminaire

A sleek general-purpose LED luminaire for dry indoor spaces. Create indirect lighting by placing the LED Jatkos on top of a cabinet, for example. These lights can be connected in sequence up to 112 W either by attaching the luminaires directly to each other or with the provided 100 mm intermediate cord. Continuous lighting without dark spots. Beam width of 160°. Surface installation. Plug connection and a 1.8 m cord. On/off switch on the luminaire. Four different lengths available.

Led Jatkos Surface mounted luminaire 18W 3000K
1850lm No dim; IP20; Protection cl. II; L70B50 30000h;
LED not exchangeable; CRI>80; SDCM6; Through-wired; Housing Plastic; Colour wh; Cover Plastic, opal



1149 IP20 18W/830 PCO WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|------|----------------|
| 4146715 | A1KYKV | 0.18 | Led Jatkos |

| Mounting | |
|--|---------------|
| Suitable for wall mounting | Yes |
| Suitable for suspended mounting | No |
| Suitable for ceiling mounting | Yes |
| Suitable for built-in mounting | No |
| Suitable for surface mounting | Yes |
| Suitable for light line configuration | Yes |
| Fit for monitor workplace | No |
| Degree of protection (IP) | IP20 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Suitable for emergency lighting | No |
| Type of wiring | Through-wired |
| Number of poles | 2 |
| Connection type | Plug |

| Structure | |
|--|----------------------|
| Lamp type | LED not exchangeable |
| With lamp | Yes |
| Suitable for number of lamps | 1 |
| Lamp holder | Other |
| Housing material | Plastic |
| Housing surface protection | Plastic-coated |
| Colour housing | White |
| Material cover | Plastic, opal |
| Type of grid | None |
| Control gear included | Yes |
| Exchangeable control gear | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | E |
| Emergency power supply integrated | No |
| With air slots | No |
| Filament test according to IEC 60695-2-11 | 650 °C - 30 s |

| Dimming and control | |
|---|-----|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI-2 | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming phase cut-off | No |
| Dimming phase cut-on | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| Dimming depending on control gear | No |
| No dimming function | Yes |
| With movement sensor | No |
| With light sensor | No |
| Constant luminous flux control | No |
| Bluetooth operated | No |
| Compatible with Casambi | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|-------------------------------------|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Beam angle | Open beam |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Light outlet | Direct |
| Effective luminous flux (lm) | 1850 |
| Colour of light (alphanumeric) | White |
| Colour temperature (min) (K) | 3000 |
| Colour temperature (max) (K) | 3000 |
| Colour rendering index CRI | 80-89 |
| Colour temperature switchable | No |
| Luminous flux adjustable | No |
| Beam angle adjustable | No |

| Lifetime and capacity | |
|--|-------|
| Rated life time L70/B50 at 25 °C | 30000 |
| Rated ambient temperature acc. IEC62722-2-1 (min) [°C] | 0 |
| Rated ambient temperature acc. IEC62722-2-1 (max) [°C] | 25 |

| Measurements | |
|-------------------|------|
| Width (mm) | 23 |
| Height/depth (mm) | 37 |
| Length (mm) | 1149 |

| Electrotechnical data | |
|-----------------------------------|---|
| Voltage type | AC |
| Nominal voltage (min) [V] | 220 |
| Nominal voltage (max) [V] | 240 |
| Type of control gear | LED operating device current-controlled |
| Protection class | II |
| Suitable for lamp power (min) [W] | 18 |
| Suitable for lamp power (max) [W] | 18 |
| Maximum system power [W] | 18 |
| Luminaire efficacy (lm/W) | 103 |