



HMIGTO1310 (45 239 92)

HMIGTO 3,5" TFT farve 320*240, Eth



Last ned produktdatablad for HMIGTO1310



[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dimensions Drawings](#) | [Mounting and Clearance](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

 Skjul

Produktspekter	Magelis GTO
Produkt eller komponent type	Avansert berøringsskjermpanel
Displayfarge	65 536 farger
Visningsstørrelse	3.5 tommer
Supply	Ekstern kilde
Kontrollknappen typen	Push-button, nøkkel type , marking: F1...F6, number of function keys = 6 (operation defined using Vijeo Designer)
Operativsystem	Magelis
Batteri type	Lithium battery for internal RAM, autonomy: 100 days, charging time = 5 d, battery life = 10 år

Komplementær

 Skjul

Terminal type	Touchscreen display
Skjermtypen	Bakgrunnsbelysning, farge TFT LCD
Skjermopløsning	320 x 240 pixels QVGA
Berøringssensitiv sone	1024 x 1024
Berøringspanel	Resistive film, 1000000 sykluser
Levetid for bakgrunnsbelysning	50000 timer (white) på 25 °C
Lysstyrke	16 nivåer - control by touch panel 16 nivåer - control by software
Character font	ASCII (europisk tegnsett) Kinesisk (forenklet kinesisk) Japansk (ANK, Kanji) Korean Taiwansk (tradisjonell kinesisk)
[Us] merkespenning	24 V DC
Spenningsgrenser	19.2...28.8 V
Startstrøm	<= 30 A
Strømforbruk i W	<= 9.6 W <= 5.2 W (when power is not supplied to external devices) <= 4.2 W (when backlight is OFF) <= 4.3 W (when backlight is dimmed)
Lokal varsling	Status LED (Orange) blinkende software starting up Status LED (grønn) klar offline Status LED (grønn) klar drift Status LED (rød) klar power supply (ON) Status LED (klar) faded power supply (OFF)
Software type	Vijeo Designer konfigurere software >= V6.1
Memory description	96 MB blits (EPROM)
Data sikkerhetskopieres	512 kB internal RAM (SRAM)
Datalagring utstyr	SD card <= 32 GB SDHC card <= 32 GB
Nedlastbare protokoller	Modbus Schneider Electric Modicon Tredje part protokoll Mitsubishi Melsec Tredje part protokoll Omron Sysmac Tredje part protokoll Rockwell Automation Allen-Bradley Tredje part protokoll Siemens Simatic Uni-TE Schneider Electric Modicon Modbus Plus Schneider Electric Modicon Fipway Schneider Electric Modicon Modbus TCP Schneider Electric Modicon

Integrert tilkoblingstype	COM1 serial link RJ45, interface: RS232C/RS485, transmission rate: 2400...115200 bps COM1 serial link RJ45, interface: RS232C/RS485, transmission rate: 187.5 kbps kompatibel med Siemens MPI ETHERNET RJ45, interface: 10 BASE-T/10 0BASE-TX ETHERNET RJ45, interface: IEEE 802.3 USB 2.0 type A USB 2.0 type mini B
Product mounting	Innfelt montering
Festemetode	Med 4 skruklemmer
Front material	PPT
Kapslingsmateriale	PPT
Kjølemetode	Naturlig konveksjon
Bredde	132 mm
Høyde	106 mm
Dybde	42 mm
Vekt	0.4 kg

Miljø

 Skjul

Standarder	EN 61131-2 IEC 61000-6-2 UL 508
Produktsertifikater	CE C-Tick CULus KCC
Omgivelsestemperatur drift	0...50 °C
Omgivende lufttemperatur for oppbevaring	-20...60 °C
Relativ fuktighet	10...90 % uten kondens
Operating altitude	< 2000 m
IP-grad	IP20 bakside på panel conforming to IEC 60529 IP65 front panel conforming to IEC 60529
NEMA beskyttelsesgrad	NEMA 4X front panel (innendørs bruk)
Støtmotstand	147 m/s ² 3 chocks in each direction X, Y and Z conforming to EN/IEC 61131-2
Vibrasjonsmotstand	3,5 mm (f = 5...9 Hz) conforming to EN/IEC 61131-2 X, Y, Z directions for 10 cycles (approx. 100 min) 1 gn (f = 9...150 Hz) conforming to EN/IEC 61131-2 X, Y, Z directions for 10 cycles (approx. 100 min)
Motstand mot elektrostatisk utladning	6 kV contact discharge conforming to IEC 61000-4-2 level 3

Bærekraftig

 Skjul

Bærekraftig	Green Premium produkt
RoHS (datokode: YYWW)	Compliant - since 1348 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Produktets miljøprofil	Tilgjengelig
Destruksjons-instruks	Tilgjengelig