

Data Sheet | Item Number: 887-850
Splicing Connector Set; L-BOXX® Mini; 221 Series

<https://www.wago.com/887-850>



This item includes:

 Item No.: 221-412 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-413 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-415 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-500 2 Mounting carrier; 221 Series - 4 mm ² ; for DIN-35 rail mounting/screw mounting; orange
 Item No.: 221-2411 Inline splicing connector with lever; for all conductor types; max. 4 mm ² ; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-2503 1 Mounting carrier with strain relief; 3-way; for inline splicing connector with lever; for screw mounting; gray	 Item No.: 221-2502 1 Mounting carrier with strain relief; 2-way; for inline splicing connector with lever; for screw mounting; gray	

Material data

Note (material data)	Information on material specifications can be found here
Fire load	15.823 MJ
Weight	899.8 g

Commercial data

PU (SPU)	1 pcs
Country of origin	DE
GTIN	4066966194968
Customs tariff number	85369010000

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product
Compliance 887-850



Documentation

Additional Information

Technical Section

pdf
2142.18 KB

