



TCSESM063F2CU1 (64 050 38)

Switch 6 TX/2 FX-MM, Extended



[Last ned produktdatablad for TCSESM063F2CU1](#)

[Endre dine utvalgskriterier](#) [Produktliste](#)

Finn andre produkter og
tilbehør



Finn ditt Schneider Electric verktøy

[Karakteristikk](#) | [Dokumenter og nedlastning](#)

Teknisk informasjon

[Skjul](#)

Produktspekter	ConneXium
Produkt eller komponent type	Ethernet TCP/IP managed switch
Konsept	Transparent Ready
Kommunikasjonsprotokoll	Ethernet TCP/IP
Port Ethernet	100base-FX - 2 port(s) fiberoptikk 10 BASE-T/10 0BASE-TX - 6 port(s) copper cable
Maksimalt antall brytere i kaskade	Ubegrenset

Komplementær

[Skjul](#)

Integrert tilkoblingstype	Duplex SC fiberoptikk Shielded RJ45 copper cable
Ekstern kommunikasjon	Twisted shielded pairs cable CAT 5E for copper cable Multimode optical fiber for fiberoptikk
Kabellengde mellom enheter	100 m copper cable
Demping	11 dB 62.2/125 µm 8 dB 50/125 µm
Ethernet service	Konfigurasjon via web server Data stream control FDR IGMP Snooping Multicast filtering Priority port Rapid Scanning Tree Protocol (RSTP) Secure port SMTP V3 SNTP client VLAN
Maksimalt antall brytere i en ring	50
Redundancy	Redundant power supplies Redundant single ring Ring coupling
[Us] merkespenning	12...48 V
Spenningsgrenser	10...60 V DC SELV
Effektforbruk	12 W
Elektrisk tilkobling	2 removable connectors 2 veis strømforsyning
Montering	35 mm symmetrical DIN rail
Merking	CE
Lokal varsling	1 LED FAULT 2 LEDs P1 P2 power supplies 1 LED ring manager 1 LED stand-by 1 LED per channel copper port activity 1 LED per channel copper port status
Alarm output	2 voltfree contact 1 A
Alarmfunksjon	Feil på strømforsyning Data link status Høy temperatur
Ethernett kablingssystem	TF switches
Bredde	120 mm
Høyde	137 mm
Dybde	115 mm
Vekt	1 kg

Miljø

[Skjul](#)

Omgivelsestemperatur drift 0...60 °C

Relativ fuktighet > 0...95 % uten kondens

IP-grad IP30

Standarder
EN/IEC 61131-2
IEC 61850-3
UL 1604 Class 1 Division 2
UL 508
CSA C22.2 No 213 Class I Division 2
CSA C22.2 No 214

Produktsertifikater
BV
C-Tick
GL
LR

Bærekraftig

[Skjul](#)

Bærekraftig Ikke et Green Premium produkt

RoHS (datokode: YYWW) Compliant - since 1022 - Schneider Electric declaration of conformity